

Product data sheet

Characteristics

100SV82A

TRFMR DRY 1PH .1KVA 240X480V-24/48V

Product availability : Stock - Normally stocked in distribution facility



Price* : 344.00 USD



Main

Product	Buck and Boost Transformer
Enclosure Code	2A
Enclosure Type	NEMA 3R
Insulation Temperature	221 °F (105 °C)
Primary Voltage	240 x 480 V
Power Rating	0.1 kVA
Secondary Voltage	24/48 V
Temperature Rise	55 °C

Ordering and shipping details

Category	16265 - BUCK & BOOST
Discount Schedule	PE2
GTIN	00785901703044
Nbr. of units in pkg.	1
Package weight(Lbs)	4.5
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

California proposition 65	WARNING: This product can expose you to chemicals including:
----- Substance 1	Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
----- More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------