



Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	1L + N
Length in 18 mm modules	18

Complementary

Number of ways	18 ways N + 1 L
Poles configuration for 1 way	1 x 1P + N 1 x 2P
Connection pitch	9 mm
Connector type	Tooth
Distance between way	18 mm
Marking	N L
Insulation	Insulated
Device presentation	Cuttable
[I _e] rated operational current	80 A (40 °C)
System Voltage	230 V AC Ph/N
[U _i] rated insulation voltage	440 V AC conforming to IEC 61439-1
[U _{imp}] rated impulse withstand voltage	6 kV
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	36
Width	12.6 in (320 mm)
Colour	Light grey (RAL 7035)
Range compatibility	Multi 9 N40 Acti 9 C40 Acti 9 ID C40 Acti 9 C40 Vigi Multi 9 N40 Vigi / N40 Vigi Acti 9 iDPN N Arc Acti 9 iARC DPNN

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	IEC 60947-7 EN/IEC 60439-1
Fire resistance	1760 °F (960 °C) (30 s) conforming to IEC 60695-2-1
Pollution degree	3 conforming to IEC 60947-7

Contractual warranty

Warranty period	18 months
-----------------	-----------