Product data sheet

Specifications





Multi9 - C60 UL1077 - MCB - 1P - 40 A - B Curve - 277 V - 5 kA

24122

- ! Discontinued on: Sep 8, 2020
- ! End-of-service on: Sep 22, 2020

① Discontinued

Main

| Range | Multi9 |
|---------------------------|---|
| Product Name | Multi9 C60 |
| Product Or Component Type | Miniature circuit-breaker |
| Device Short Name | C60 UL1077 |
| Device Application | Distribution |
| Poles Description | 1P |
| Number Of Protected Poles | 1 |
| Line Rated Current | 40 A 77 °F (25 °C) |
| Network Type | AC DC |
| Trip Unit Technology | Thermal-magnetic |
| Curve Code | В |
| Breaking Capacity | 10 kA Icu 240 V AC EN/IEC 60947-2 10 kA Icu 240 V AC GB 14048.2 5 kA AIR 277 V AC UL 1077 10 kA AIR 240 V AC UL 1077 10 kA AIR 65 V DC UL 1077 3 kA Icu 415 V AC EN/IEC 60947-2 10 kA Icu 60 V DC EN/IEC 60947-2 3 kA Icu 415 V AC GB 14048.2 10 kA Icu 60 V DC GB 14048.2 5 kA AIR 277 V AC CSA C22.2 No 235 10 kA AIR 240 V AC CSA C22.2 No 235 |
| Suitability For Isolation | Yes EN/IEC 60947-2 |

Complementary

| Network Frequency | 50/60 Hz |
|---|--|
| [Ue] Rated Operational Voltage | 415 V AC 240 V AC 60 V DC |
| Magnetic Tripping Limit | 4 x ln +/- 20 % AC 5.6 x ln +/- 20 % DC |
| Limitation Class | 3 EN/IEC 60947-2 |
| [Ui] Rated Insulation Voltage | 500 V AC EN/IEC 60947-2 |
| [Uimp] Rated Impulse Withstand Voltage | 6 kVEN/IEC 60947-2 |
| Contact Position Indicator | Yes |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Control Type | Toggle |
|--------------------------|---|
| Local Signalling | ON/OFF indication |
| Mounting Mode | Clip-on |
| Mounting Support | DIN rail |
| 9 Mm Pitches | 2 |
| Height | 3.19 in (81 mm) |
| Width | 0.71 in (18 mm) |
| Depth | 2.87 in (73 mm) |
| Net Weight | 0.24 lb(US) (0.11 kg) |
| Color | Gray |
| Mechanical Durability | 20000 cycles |
| Electrical Durability | 10000 cycles |
| Provision For Padlocking | Padlockable |
| Connections - Terminals | Tunnel type terminal top or bottom) 0.000.05 in² (2.535 mm²) AWG 14AWG 2) - rigid |
| Wire Stripping Length | 0.55 in (14 mm) for top or bottom connection |
| Tightening Torque | 30.98 lbf.in (3.5 N.m) top or bottom |

Environment

| Standards | UL 1077 GB 14048.2 EN/IEC 60947-2 CSA C22.2 No 235 |
|---------------------------------------|---|
| Product Certifications | UR CSA CCC IEC |
| Ip Degree Of Protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution Degree | 3 EN/IEC 60947-2 |
| Overvoltage Category | IV |
| Tropicalisation | 2 IEC 60068-1 |
| Relative Humidity | 95 % 131 °F (55 °C) |
| Operating Altitude | 6561.68 ft (2000 m) |
| Ambient Air Temperature For Operation | -22158 °F (-3070 °C) |
| Ambient Air Temperature For Storage | -40176 °F (-4080 °C) |

Ordering and shipping details

| Category | 99999-DEFAULT ADD CATEGORY |
|-------------------|----------------------------|
| Discount Schedule | N/A |
| Gtin | 785901880233 |
| Returnability | No |

Packing Units

Unit Type Of Package 1 PCE

| Number Of Units In Package 1 | 1 |
|------------------------------|---------------------|
| Package 1 Height | 0.79 in (2 cm) |
| Package 1 Width | 3.19 in (8.1 cm) |
| Package 1 Length | 3.58 in (9.1 cm) |
| Package 1 Weight | 4.25 oz (120.491 g) |

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance

| ② | Mercury Free | |
|----------|----------------------------|-----|
| ⊘ | Rohs Exemption Information | Yes |
| ⊘ | Halogen Free Product | |

Certifications & Standards

| Eu Rohs Directive | Compliant |
|-----------------------|--|
| | EU RoHS Declaration |
| | |
| China Rohs Regulation | China RoHS declaration |
| | Product out of China RoHS scope. Substance declaration for your information. |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |