Product data sheet

Specifications

Green Premium™

voltage release - MX + OF - 1 NO/ NC 110..277 V AC - 110...130 V DC - for C60

27109

Discontinued on: Jul 12, 2021

Discontinued

Main

Range Of Product	Multi9
Product Or Component Type	Shunt trip release with OC contact
Device Short Name	MX + OF
Signal Contacts Composition	1 C/O
Line Rated Current	1 A at 277 V, AC 50/60 Hz 0.3 A at 110 V, DC 0.3 A at 125 V, DC 0.4 A at 120 V, AC 50/60 Hz 0.8 A at 240 V, AC 50/60 Hz
[Uc] Control Circuit Voltage	110...277 V AC 50/60 Hz 110...130 V DC
9 Mm Pitches	2

Complementary

Range Compatibility	Multi 9 Multi9 C60 Multi 9 Multi9 C60H-DC
Impulse Duration	8 ms
Local Signalling	Action indicator
Mounting Mode	Fixed
Mounting Support	35 mm symmetrical DIN rail
Height	3.25 in (82.5 mm)
Width	0.71 in (18 mm)
Depth	2.68 in (68 mm)
Connections - Terminals	Pad terminal - 1 0.00 in² (2.5 mm²) - flexible
Wire Stripping Length	0.35 in (9 mm)
Tightening Torque	8.85 lbf.in (1 N.m)

Environment

Standards	UL 489 EN/IEC 60947-5-1
Product Certifications	ASTA LCIE KEMA ASEFA
Tropicalisation	2 EN/IEC 60947-5-1

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative Humidity	95 % 131 °F (55 °C)
Ambient Air Temperature For Operation	-13…122 °F (-25…50 °C)
Ambient Air Temperature For Storage	-40…185 °F (-40…85 °C)

Ordering and shipping details

Category	00908-C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
Gtin	3303430271093
Returnability	No
Country Of Origin	BE

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.54 in (9 cm)
Package 1 Width	0.94 in (2.4 cm)
Package 1 Length	3.15 in (8 cm)
Package 1 Weight	2.57 oz (73 g)

Contractual warranty

Warranty	18 months

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc	
Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.