Product data sheet





voltage release - MX + OF1 NO/ NC - 24 V AC / 12..24 V DC - for C60

27118

Discontinued on: Mar 15, 2022



Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Of Product	Multi9
Product Or Component Type	Shunt trip release with OC contact
Device Short Name	MX + OF
Signal Contacts Composition	1 C/O
Line Rated Current	2.5 A at 12 V, DC
	5.6 A at 24 V, DC
	7.7 A at 24 V, AC 50/60 Hz
[Uc] Control Circuit Voltage	24 V AC 50/60 Hz
	1224 V DC
9 Mm Pitches	2

Complementary

Range Compatibility	Multi 9 Multi9 C60 Multi 9 Multi9 C60H-DC	
Impulse Duration	8 ms	
Local Signalling	Action indicator	
Mounting Mode	Fixed	
Mounting Support	35 mm symmetrical DIN rail	
Height	3.25 in (82.5 mm)	
Width	0.71 in (18 mm)	
Depth	2.68 in (68 mm)	
Connections - Terminals	Pad terminal - 1 0.00 in² (2.5 mm²) - flexible	
Wire Stripping Length	0.35 in (9 mm)	
Tightening Torque	8.85 lbf.in (1 N.m)	

Environment

Standards	EN/IEC 60947-5-1 UL 489
Product Certifications	ASEFA KEMA ASTA LCIE
Tropicalisation	2 EN/IEC 60947-5-1
Relative Humidity	95 % 131 °F (55 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature For Operation	-13122 °F (-2550 °C)
Ambient Air Temperature For Storage	-40185 °F (-4085 °C)

Ordering and shipping details

Category	US10DE200908
Discount Schedule	0DE2
Gtin	3303430271185
Returnability	No
Country Of Origin	US

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.54 in (9 cm)
Package 1 Width	0.94 in (2.4 cm)
Package 1 Length	3.15 in (8 cm)
Package 1 Weight	2.12 oz (60 g)

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
9	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.