

Enercept power monitoring - unit basic 300 A small

3020B032S

! Discontinued

Main

Range	PowerLogic
Product Name	PowerLogic Enercept
Device Short Name	Enercept
Product Or Component Type	Power meter
Device Application	Sub billing Power monitoring
Variant	Basic
Power Monitoring	Basic instrumentation
Type Of Measurement	Active energy Active power
[Us] Rated Supply Voltage	208480 V AC 50/60 Hz
Network Frequency	60 Hz 50 Hz

Complementary

Current Transformer Type	Split core balance
Current Transformer Input	Split core CT 0300 A
Measurement Voltage	208480 V
Measurement Accuracy	+/- 1 % 10100 %
Communication Port Protocol	Modbus RTU
Communication Port Support	RS485
Communication Network Type	Modbus RTU
Mounting Mode	Direct

Environment

Ambient Air Temperature For Operation	32140 °F (060 °C)
Relative Humidity	95 %
Product Certifications	CUL UL
Width	Internal 1.22 in (31 mm) External 4.76 in (121 mm)
Depth	1.18 in (30 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	Internal 1.18 in (30 mm) External 3.94 in (100 mm)
Net Weight	2 20 lb(US) (1 kg)

Ordering and shipping details

Category	09791-POWERLOGIC ENERCEPT POWER METER
Discount Schedule	PL1
Returnability	No
Country Of Origin	US

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive

Not compliant