# **Product data sheet**

Specifications



# NEMA Control Relay, Type X, timing, 3 minute on delay, 10A resistive at 600 VAC, 4 normally open, 230/250 VDC coil

8501XDO40XTE2V66



(!) Discontinued on: Dec 2, 2020

(!) End-of-service on: Dec 31, 2020

## Main

Range	8501X	
Relay Type	Timing	
Product	Relay	
Current Rating	10 A AC 5 A DC	
Number Of Poles	4P	
Voltage Rating	250 V DC	

# Complementary

Complementary	
Coil Voltage	230/250 V DC
Coil Voltage Limints	Operational 0.81.1 Uc DC
Breaking Current	6 A 120 V AC inductive control circuit UL 508 3 A 240 V AC inductive control circuit UL 508 1.5 A 480 V AC inductive control circuit UL 508 1.2 A 600 V AC inductive control circuit UL 508 10 A <= 600 V AC resistive control circuit UL 508 1.1 A 125 V DC inductive control circuit UL 508 0.55 A 250 V DC inductive control circuit UL 508 0.2 A 301600 V DC inductive control circuit UL 508 4 A 125 V DC resistive control circuit UL 508 0.8 A 250 V DC resistive control circuit UL 508
Making Current	$60 \ A \ 120 \ V \ AC$ inductive control circuit UL 508 $30 \ A \ 240 \ V \ AC$ inductive control circuit UL 508 $15 \ A \ 480 \ V \ AC$ inductive control circuit UL 508 $12 \ A \ 600 \ V \ AC$ inductive control circuit UL 508 $10 \ A \ = \ 600 \ V \ AC$ resistive control circuit UL 508 $1.1 \ A \ 125 \ V \ DC$ inductive control circuit UL 508 $0.55 \ A \ 250 \ V \ DC$ inductive control circuit UL 508 $0.2 \ A \ 301600 \ V \ DC$ inductive control circuit UL 508 $4 \ A \ 125 \ V \ DC$ inductive control circuit UL 508 $0.2 \ A \ 301600 \ V \ DC$ inductive control circuit UL 508 $0.8 \ A \ 250 \ V \ DC$ resistive control circuit UL 508 $0.8 \ A \ 250 \ V \ DC$ resistive control circuit UL 508 $0.8 \ A \ 250 \ V \ DC$ resistive control circuit UL 508
Time Delay Type	On-delay
Time Delay Time	5180 s
Coil Inrush In Watts	18 W
Coil Sealed Power In Watts	18 W
Device Operating Time	37 ms - pick-up 21 ms - drop-out
Contact Configuration	4 NO 4 standard contact cartridges

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Electrical Connection	Screw clamp terminals
Wire Gauge	AWG 18AWG 12 copper
Terminal Tightening Torque	Control circuit 9.0312.04 lbf.in (1.021.36 N.m) screw terminal
Mounting Type	Panel
Operating Temperature Range	-40160 °F (-4071 °C)
Height	3.56 in (90.42 mm)
Width	2.23 in (56.64 mm)
Depth	7.77 in (197.36 mm)

#### Environment

Product Certifications

CSA LR60905 class 3211 03 UL listed file E78403 CCN NKCR

# Ordering and shipping details

Category	21157-8501 XDO (DC)
Discount Schedule	CP2
Gtin	00785901340577
Returnability	No
Country Of Origin	MX

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

## **Contractual warranty**

Warranty

18 months

# Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free

Rohs Exemption Information Yes

## **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov