## Product data sheet

Specifications

# Schneider Electric SQUARE 8501XO20V02Y414 Picture



NEMA Control Relay, Type X, machine tool, 10A resistive at 600 VAC, 2 normally open contacts, 110/120 VAC 50/60 Hz coil

8501XO20V02Y414

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 144.00 USD

#### Main

Range	8501X	
Relay Type	Control	
Product	Relay	
Current Rating	10 A AC	
	5 A DC	

#### Complementary

Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control Circuit Voltage Limits	Operational 0.851.1 Uc AC 50/60 Hz
Rated Breaking Capacity	6 A 120 V AC inductive control circuit UL 508
	3 A 240 V AC inductive control circuit UL 508
	1.5 A 480 V AC inductive control circuit UL 508
	1.2 A 600 V AC inductive control circuit UL 508
	10 A <= 600 V AC resistive control circuit UL 508
	1.1 A 125 V DC inductive control circuit UL 508
	0.55 A 250 V DC inductive control circuit UL 508
	0.2 A 301600 V DC inductive control circuit UL 508
	4 A 125 V DC resistive control circuit UL 508
	0.8 A 250 V DC resistive control circuit UL 508
[Icm] Rated Short-Circuit Making	60 A 120 V AC inductive control circuit UL 508
Capacity	30 A 240 V AC inductive control circuit UL 508
	15 A 480 V AC inductive control circuit UL 508
	12 A 600 V AC inductive control circuit UL 508
	10 A <= 600 V AC resistive control circuit UL 508
	1.1 A 125 V DC inductive control circuit UL 508
	0.55 A 250 V DC inductive control circuit UL 508
	0.2 A 301600 V DC inductive control circuit UL 508
	4 A 125 V DC inductive control circuit UL 508
	0.8 A 250 V DC resistive control circuit UL 508
Inrush Power In Va	148 VA 60 Hz
	143 VA 50 Hz
Hold-In Power Consumption In Va	23 VA 60 Hz
	25 VA 50 Hz
Operating Time	15 ms - pick-up
	16 ms - drop-out
Contact Configuration	2 NO 2 standard contact cartridges
Electrical Connection	Ring tongue

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Awg Gauge	AWG 18AWG 12 copper	
Tightening Torque	Control circuit 9.0312.04 lbf.in (1.021.36 N.m) screw terminals	
Mounting Type	Panel	
Height	3.5 in (88.90 mm)	
Width	2.23 in (56.64 mm)	
Depth	3.95 in (100.33 mm)	

### **Environment**

Operating Temperature	-40160 °F (-4071 °C)
Certifications	CSA LR60905 class 3211 03

## Ordering and shipping details

Category	US10CP221158
Discount Schedule	0CP2
Gtin	785901001423
Returnability	No
Country Of Origin	MX

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.54 in (6.452 cm)
Package 1 Width	1.00 in (2.54 cm)
Package 1 Length	6.45 in (16.387 cm)
Package 1 Weight	33.92 oz (961.616 g)

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov