Specifications



Non-Reversing Starter Size 00, 3-Pole, Melting Alloy Overload, NEMA 1+Options

8536SAG12V02SX22

Price*: 1,044.00 USD

() Discontinued

Main

Product Type	Starter
Product Range	S
Starter Type	Non reversing

Complementary

Nema Size00Rated Current9 ANumber Of Poles3PMaximum Voltage Rating600 V ACPhase3 phaseType Of OverloadMelting alloy 3Horsepower Rating1.5 HP 200 V AC 1.5 HP 200 V AC 2 HP 460 V AC 2 HP 575 V ACCoil Voltage110 V AC 50 Hz 120 V AC 60 HzControl Circuit TypeSeparate control circuitControl UnitsNo control unitsAuxiliary Contacts2 NO + 2 NCTerminal TypeScrew clamp terminals	
Number Of Poles 3P Maximum Voltage Rating 600 V AC Phase 3 phase Type Of Overload Melting alloy 3 Horsepower Rating 1.5 HP 200 V AC 1.5 HP 230 V AC 2 HP 460 V AC 2 HP 575 V AC 2 HP 575 V AC Coil Voltage 110 V AC 50 Hz 120 V AC 60 Hz 120 V AC 60 Hz Control Circuit Type Separate control circuit Control Units No control units Auxiliary Contacts 2 NO + 2 NC	
Maximum Voltage Rating 600 V AC Phase 3 phase Type Of Overload Melting alloy 3 Horsepower Rating 1.5 HP 200 V AC 1.5 HP 230 V AC 2 HP 460 V AC 2 HP 460 V AC 2 HP 575 V AC Coil Voltage 110 V AC 50 Hz 120 V AC 60 Hz 2 Control Circuit Type Separate control circuit Control Units No control units Auxiliary Contacts 2 NO + 2 NC	
Phase 3 phase Type Of Overload Melting alloy 3 Horsepower Rating 1.5 HP 200 V AC 1.5 HP 230 V AC 2 HP 460 V AC 2 HP 460 V AC 2 HP 575 V AC Coil Voltage 110 V AC 50 Hz 120 V AC 60 Hz 120 V AC 60 Hz Control Circuit Type Separate control circuit Control Units No control units Auxiliary Contacts 2 NO + 2 NC	
Type Of Overload Melting alloy 3 Horsepower Rating 1.5 HP 200 V AC 1.5 HP 230 V AC 2 HP 460 V AC 2 HP 460 V AC 2 HP 575 V AC Coil Voltage 110 V AC 50 Hz 120 V AC 60 Hz 120 V AC 60 Hz Control Circuit Type Separate control circuit Control Units No control units Auxiliary Contacts 2 NO + 2 NC	
Horsepower Rating 1.5 HP 200 V AC 1.5 HP 230 V AC 2 HP 460 V AC 2 HP 575 V AC Coil Voltage 110 V AC 50 Hz 120 V AC 60 Hz Control Circuit Type Separate control circuit Control Units Auxiliary Contacts 2 NO + 2 NC	
1.5 HP 230 V AC 2 HP 460 V AC 2 HP 575 V AC Coil Voltage 110 V AC 50 Hz 120 V AC 60 Hz Control Circuit Type Separate control circuit Control Units No control units Auxiliary Contacts 2 NO + 2 NC	
120 V AC 60 Hz Control Circuit Type Separate control circuit Control Units No control units Auxiliary Contacts 2 NO + 2 NC	
Control Units No control units Auxiliary Contacts 2 NO + 2 NC	
Auxiliary Contacts 2 NO + 2 NC	
Terminal Type Screw clamp terminals	
Height 10.00 in (254 mm)	
Width 5.98 in (152 mm)	
Depth 5.55 in (141 mm)	

Environment

Enclosure Type	NEMA 1 painted sheet steel
Certifications	NEMA CSA UL Listed

Ordering and shipping details

Discount Schedule	CP1
Returnability	No

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

US
PCE
1
6.00 lb(US) (2.722 kg)
-

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

California Proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov