



Non-Reversing Starter Size 2, 2-Pole, Melting Alloy Overload, NEMA 1 +Options

8536SDG6V80CFF4P21TX30

Main

| Product Type | Starter |
|---------------|---------------|
| Product Range | S |
| Starter Type | Non reversing |

Complementary

| Nema Size | 2 |
|------------------------|--|
| Rated Current | 45 A |
| Number Of Poles | 2P |
| Maximum Voltage Rating | 600 V AC |
| Phase | 1 phase |
| Type Of Overload | Melting alloy 1 |
| Horsepower Rating | 3 HP 115 V AC 7.5 HP 230 V AC |
| Coil Voltage | 240 V AC 60 Hz primary circuit 120 V AC 60 Hz secondary circuit |
| Control Circuit Type | Control circuit transformer |
| Control Units | Selector switch (HAND-OFF-AUTO) |
| Pilot Light | Red indicator on incandescent push-to-test |
| Auxiliary Contacts | 3 NO |
| Other Equipment | 2 fuses (primary), 1 fuse (secondary) |
| Terminal Type | Screw clamp terminals |

Environment

| Enclosure Type | NEMA 1 painted sheet steel |
|----------------|----------------------------|
| Certifications | CSA |
| | NEMA |
| | UL Listed |

Ordering and shipping details

| Category | 21192-8502,36 SC,SD(NOT S*R,T,W) |
|-------------------|----------------------------------|
| Discount Schedule | CP1 |
| Returnability | No |
| Country Of Origin | MX |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Contractual warranty

Warranty

18 months