

# AUTOTRFMR STARTER 600VAC 90A

8606SEG1GV81S

! To be discontinued on: Sep 30, 2024

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Device Short Name S

! To be discontinued

## Complementary

[Ue] Rated Operational Voltage	480 V AC
[Uc] Control Circuit Voltage	120 V AC
Depth	16 in (406.40 mm)
Device Mounting	Surface
Height	70 in (1778.00 mm)
Maximum Horse Power Rating	30 hp
Nema Size	3
Number Of Poles	3
Number Of Thermal Units Required	3
Net Weight	490 lb(US) (222.26 kg)
Width	32 in (812.80 mm)

### **Environment**

Nema Degree Of Protection	NEMA 1
Product Certifications	UL listed file E70074 CCN NLDX

## Ordering and shipping details

Category	21231 - 8606 (NOT S*K)
Discount Schedule	CP1
Returnability	No
Country Of Origin	MX

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	70.00 in (177.8 cm)
Package 1 Width	32.01 in (81.3 cm)
Package 1 Length	15.98 in (40.6 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Weight

525.00 lb(US) (238.136 kg)

## **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive	Not compliant
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov