

AUTOTRFMR STARTER 600VAC 270AMP

8606SGA1PV06

! To be discontinued on: Sep 30, 2024

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Device Short Name S

! To be discontinued

Complementary

Rated Current	270 A
[Ue] Rated Operational Voltage	480 V AC
[Uc] Control Circuit Voltage	480 V AC
Depth	16 in (406.40 mm)
Device Mounting	Surface
Height	70 in (1778.00 mm)
Maximum Horse Power Rating	150 hp
Nema Size	5
Number Of Poles	3
Number Of Thermal Units Required	3
Net Weight	635 lb(US) (288.03 kg)
Width	32 in (812.80 mm)

Environment

Nema Degree Of Protection	NEMA 12
Product Certifications	UL listed file E70074 CCN NLDX

Ordering and shipping details

Category	21231 - 8606 (NOT S*K)
Discount Schedule	CP1
Returnability	No
Country Of Origin	MX

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	70.00 in (177.8 cm)
Package 1 Width	32.01 in (81.3 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Length	15.98 in (40.6 cm)
Package 1 Weight	600.00 lb(US) (272.155 kg)

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive	Not compliant
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov