Specifications



NEMA Starter, Type S, reversing, horizontal, Size 00, 9A, 1 HP at 230 VAC, 5 kA SSCR, 1 phase, 3 pole, melting alloy overload, 120 VAC coil, open

8736SAO14V02

! To be discontinued on: Sep 30, 2024

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Product Type	Starter
Product Range	S
Starter Type	Reversing

#### Complementary

00
9 A
3P
Horizontal
4 wires
600 V AC
1 phase
Repulsion induction
Melting alloy 1
0.33 HP 115 V AC 1 HP 230 V AC
Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC
110 V AC 50 Hz 120 V AC 60 Hz
Common control circuit
No control units
Without pilot light
Without
Screw clamp terminals
6.91 in (175.51 mm)
7.13 in (181.10 mm)
5.31 in (134.87 mm)

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

# Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed CSA

# Ordering and shipping details

Category	21271 - 8702,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
Gtin	785901747543
Returnability	No
Country Of Origin	MX

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.93 in (17.6 cm)
Package 1 Width	7.13 in (18.1 cm)
Package 1 Length	5.31 in (13.5 cm)
Package 1 Weight	8.00 lb(US) (3.629 kg)

### **Contractual warranty**

Warranty

18 months

#### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

**Eu Rohs Directive** 

Under investigation