# Product data sheet

Specifications



### 8903L electrically held lighting contactor, 2 P, 2 NO, 30 A, 600 V, 440/480 V 50/60 Hz coil, NEMA 1

8903LG20V06

() Discontinued on: Oct 15, 2021

Product availability: Non-Stock - Not normally stocked in distribution facility

### Main

Product Or Component Type	Electrically Held Lighting Contactor	
Range Of Product	8903L	
Control Circuit	Separate control circuit	

### Complementary

Control Circuit Voltage440 V AC 50 Hz 480 V AC 60 HzInrush Power In Va150 VA 60 Hz 150 VA 50 HzHold-In Power Consumption In Va 30 VA 60 Hz 30 VA 50 Hz30 VA 60 Hz 30 VA 50 HzCurrent Rating20 A tungsten 30 A fluorescentNumber Of Poles2P 2 NOControl UnitNo control unitsPilot LightNo indicatorElectrical ConnectionScrew-clamp terminalsHeight12.68 in (322 mm)Depth6.02 in (153 mm)		
How		
30 VA 50 Hz     Current Rating   20 A tungsten 30 A fluorescent     Number Of Poles   2P 2 NO     Control Unit   No control units     Pilot Light   No indicator     Electrical Connection   Screw-clamp terminals     Height   12.68 in (322 mm)		
30 A fluorescent   Number Of Poles 2P 2 NO   Control Unit No control units   Pilot Light No indicator   Electrical Connection Screw-clamp terminals   Height 12.68 in (322 mm)		
Control Unit No control units   Pilot Light No indicator   Electrical Connection Screw-clamp terminals   Height 12.68 in (322 mm)		
Pilot Light No indicator   Electrical Connection Screw-clamp terminals   Height 12.68 in (322 mm)		
Electrical Connection Screw-clamp terminals   Height 12.68 in (322 mm)		
Height     12.68 in (322 mm)		
	Screw-clamp terminals	
Depth 6 02 in (153 mm)		
Width     7.80 in (198 mm)		

#### Environment

Enclosure Type	NEMA 1 painted sheet steel surface
Product Certifications	UL Listed CSA

### Ordering and shipping details

Category	21321 - 8903 L (NOT LX)
Discount Schedule	CP1
Gtin	785901022633
Returnability	No
Country Of Origin	MX

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.50 in (19.05 cm)
Package 1 Width	8.00 in (20.32 cm)
Package 1 Length	13.50 in (34.29 cm)
Package 1 Weight	12.20 lb(US) (5.535 kg)

### **Contractual warranty**

Warranty

18 months

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc
Mercury Free
Rohs Exemption Information Yes
Pvc Free
Halogen Free Plastic Parts Product

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile