# Product data sheet

Specifications



## 8903L electrically held lighting contactor, 12 P, 4 NO, 8 NC, 30 A, 600 V, 110/120 V 50/60 Hz coil, NEMA 1

8903LG408V02

() Discontinued on: Oct 15, 2021

# Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Product Or Component Type	Electrically Held Lighting Contactor	
Range Of Product	8903L	
Control Circuit	Separate control circuit	
Complementary		
Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Inrush Power In Va	180 VA 60 Hz 170 VA 50 Hz	
Hold-In Power Consumption In Va	35 VA 60 Hz	

35 VA 50 Hz     Current Rating   20 A tungsten 30 A fluorescent     Number Of Poles   4P 4 NO     Control Unit   No control units     Pilot Light   No indicator     Electrical Connection   Screw-clamp terminals     Height   12.68 in (322 mm)     Depth   6.02 in (153 mm)		
30 A fluorescent     Number Of Poles   4P 4 NO     Control Unit   No control units     Pilot Light   No indicator     Electrical Connection   Screw-clamp terminals     Height   12.68 in (322 mm)     Depth   6.02 in (153 mm)	Hold-In Power Consumption In Va	
Control Unit No control units   Pilot Light No indicator   Electrical Connection Screw-clamp terminals   Height 12.68 in (322 mm)   Depth 6.02 in (153 mm)	Current Rating	•
Pilot Light No indicator   Electrical Connection Screw-clamp terminals   Height 12.68 in (322 mm)   Depth 6.02 in (153 mm)	Number Of Poles	4P 4 NO
Electrical Connection Screw-clamp terminals   Height 12.68 in (322 mm)   Depth 6.02 in (153 mm)	Control Unit	No control units
Height     12.68 in (322 mm)       Depth     6.02 in (153 mm)	Pilot Light	No indicator
Depth     6.02 in (153 mm)	Electrical Connection	Screw-clamp terminals
	Height	12.68 in (322 mm)
Width     7.80 in (198 mm)	Depth	6.02 in (153 mm)
	Width	7.80 in (198 mm)

### Environment

Enclosure Type	NEMA 1 painted sheet steel surface
Product Certifications	UL Listed CSA

### Ordering and shipping details

Category	21321 - 8903 L (NOT LX)	
Discount Schedule	CP1	
Returnability	No	
Country Of Origin	МХ	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12.68 in (32.2 cm)
Package 1 Width	7.80 in (19.8 cm)
Package 1 Length	6.02 in (15.3 cm)
Package 1 Weight	11.00 lb(US) (4.99 kg)

## **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

## Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free
Halogen Free Plastic Parts Product

#### **Certifications & Standards**

Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile