



## **CONTACTOR 600VAC 50AMP DPA +OPTIONS**

8910DPA53V09DFG1Y135

#### Main

Device Short Name DPA

# Complementary

	<u>'</u>	
Line Rated Current	50 A	
Depth	3.67 in (93.22 mm)	
Height	4.06 in (103.12 mm)	
Locked Rotor Rated Current	300 A 230 V AC	
	250 A 460 V AC	
	200 A 575 V AC	
Maximum Horse Power Rating	3 hp 115 V AC, 1 phase	
	10 hp 230 V AC, 1 phase	
	15 hp 230 V AC, 3 phase	
	30 hp 460/575 V AC, 3 phase	
Mounting Support	panel	
Number Of Poles	3	
Width	2.56 in (65.02 mm)	

#### **Environment**

**Product Certifications** UL listed file E42240 CCN NLDX CSA LR25490 class 3211 04

## Ordering and shipping details

Category	21345-8910 DPA 5_(50 AMP)
Discount Schedule	CP1B
Returnability	No
Country Of Origin	MX

### **Contractual warranty**

Warranty 18 months

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
California Proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov