# Product data sheet

Specifications



## PUSHBUTTON OPERATOR 30MM TYPE K +OPTIONS

9001K2L7G

- () Discontinued on: Dec 2, 2020
- (!) End-of-service on: Dec 31, 2020

() Discontinued

#### Main

| Range Of Product          | Harmony 9001K                    |
|---------------------------|----------------------------------|
| Product Or Component Type | Complete illuminated push-button |
| Device Short Name         | 9001K                            |
| Mounting Diameter         | 1.18 in (30 mm)                  |
| Light Source              | incandescent                     |

### Complementary

| Bezel Material               | Chromium plated metal                              |
|------------------------------|--|
| Shape Of Signaling Unit Head | Round  |
| Type Of Operator             | spring return                                      |
| Operator Profile             | Green projecting, unmarked                         |
| Bulb Base                    | BA 9s  |
| Light Block Supply           | Via integral transformer 220240 V AC 50/60 Hz 6 V) |
| Mechanical Durability        | 5000000 cycles                                     |
| Operating Position           | Any position                                       |
| Net Weight                   | 0.37 lb(US) (0.166 kg)                             |

#### Environment

| Standards                                | JIS C 4520<br>EN/IEC 60947-5-4<br>JIS C 852<br>EN/IEC 60947-1<br>CSA C22.2 No 14<br>UL 508<br>EN/IEC 60947-5-1 |  |
|--|--|--|
| Product Certifications                   | UL 508<br>NEMA   |  |
| Protective Treatment                     | тс   |  |
| Ambient Air Temperature For<br>Storage   | -40158 °F (-4070 °C)   |  |
| Ambient Air Temperature For<br>Operation | -13158 °F (-2570 °C)   |  |
| Vibration Resistance                     | 7 gn 2500 Hz)IEC 60068-2-6   |  |
| Shock Resistance                         | 50 gn IEC 60068-2-27   |  |
| Electrical Shock Protection Class        | Class II IEC 61140   |  |
| Ip Degree Of Protection                  | IP66 IEC 60529   |  |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3R NEMA 4

### Ordering and shipping details

| Category          | 21426-9001 K (NOT KA,KM,KX) |
|-------------------|-----------------------------|
| Discount Schedule | CS1                         |
| Gtin              | 00785901347729              |
| Returnability     | No                          |
| Country Of Origin | MX                          |

### **Contractual warranty**

Warranty

18 months

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Mercury Free

Rohs Exemption Information
Yes

### **Certifications & Standards**

| Reach Regulation          | REACh Declaration   |
|---------------------------|---|
| Eu Rohs Directive         | Pro-active compliance (Product out of EU RoHS legal scope)  |
| China Rohs Regulation     | China RoHS declaration  |
| Environmental Disclosure  | Product Environmental Profile   |
| Weee                      | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |
| Circularity Profile       | No need of specific recycling operations  |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |