Product data sheet

Specifications





red Ø30 emergency stop pushbutton Ø40 trigger action/turn release 1 NC

9001SKR16H6

! Discontinued on: Jan 23, 2021



Product availability: Non-Stock - Not normally stocked in distribution facility

Main

| Range Of Product | Harmony 9001SK |
|---------------------------|--------------------------------|
| Product Or Component Type | Emergency stop push-button |
| Device Short Name | 9001SK |
| Type Of Operator | Turn to release trigger action |
| Operator Profile | Ped mushroom Ø 40 mm, upmarked |

Complementary

| Bezel Material | Plastic | |
|---|---|--|
| Mounting Diameter | 1.18 in (30 mm) | |
| Cad Overall Width | 1.57 in (40 mm) | |
| Cad Overall Height | 1.57 in (40 mm) | |
| Cad Overall Depth | 4.57 in (116 mm) | |
| Net Weight | 0.31 lb(US) (0.141 kg) | |
| Operating Position | Any position | |
| Shape Of Signaling Unit Head | Round | |
| Operator Position Information | 2 positions | |
| Contacts Type And Composition | 1 NC | |
| Mechanical Durability | 5000000 cycles | |
| Connections - Terminals | Screw clamp terminals, 1 x 0.222 x 1.5 mm² EN/IEC 60947-1 | |
| Tightening Torque | 7.08 lbf.in (0.8 N.m) EN/IEC 60947-1 | |
| Shape Of Screw Head | Cross slotted | |
| Contacts Material | Silver alloy contacts | |
| Short-Circuit Protection | 10 A cartridge fuse EN/IEC 60947-5-1 | |
| [Ui] Rated Insulation Voltage | 250 V 3)EN/IEC 60947-1 | |
| [Uimp] Rated Impulse Withstand Voltage | 2.5 kV EN/IEC 60947-1 | |
| [le] Rated Operational Current | 3 A 240 V, AC-15, A600-Q600 NEMA 0.55 A 125 V, DC-13, A600-Q600 NEMA | |
| [Icm] Rated Short-Circuit Making Capacity | 12 kA 120 V AC-15, 7200 VA 0.1 kA 600 V DC-13 0.27 kA 250 V DC-13 | |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

0.55 kA 125 V DC-13



| | 1.2 kA 600 V AC-15, 720 VA 1.5 kA 480 V AC-15, 720 VA 0.1 kA 600 V DC-13 |
|---------------------|--|
| | 0.27 kA 250 V DC-13 0.55 kA 125 V DC-13 |
| Compatibility Code | 9001SK |
| Device Presentation | Complete product |

Environment

| Environment | |
|--|---|
| Protective Treatment | TC |
| Ambient Air Temperature For Storage | -40158 °F (-4070 °C) |
| Ambient Air Temperature For Operation | -13158 °F (-2570 °C) |
| Overvoltage Category | Class II IEC 61140 |
| Ip Degree Of Protection | IP66 IEC 60529 |
| Nema Degree Of Protection | NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 4 |
| Standards | EN/IEC 60204-1, for emergency stop devices if used with emergency stop legend plate type 9001KN EN/ISO 13850, for emergency stop devices if used with emergency stop legend plate type 9001KN EN/IEC 60947-5-1 EN/IEC 60947-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14 |
| Product Certifications | UL 508 NEMA |
| Vibration Resistance | 7 gn 2500 Hz)IEC 60068-2-6 |
| Shock Resistance | 50 gn IEC 60068-2-27 |

Ordering and shipping details

| Category | US10CS121426 | |
|-------------------|--------------|--|
| Discount Schedule | 0CS1 | |
| Gtin | 785901631880 | |
| Returnability | No | |
| Country Of Origin | MX | |

Packing Units

| Unit Type Of Package 1 | PCE 1 | |
|------------------------------|--------------------|--|
| Number Of Units In Package 1 | | |
| Package 1 Height | 2.50 in (6.35 cm) | |
| Package 1 Width | 2.00 in (5.08 cm) | |
| Package 1 Length | 4.50 in (11.43 cm) | |

Package 1 Weight

14.75 oz (418.212 g)

Contractual warranty

Warranty

Apr 25, 2024

18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| ② | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| ⊘ | Toxic Heavy Metal Free | |
| | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile | No need of specific recycling operations |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |