## Product data sheet

Specifications



() Discontinued

# selector switch Ø 30 - 2 positions - maintained

9001SKS12

- () Discontinued on: Dec 2, 2020
- (!) End-of-service on: Dec 31, 2020

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

| Range Of Product          | Harmony 9001SK  |
|---------------------------|-----------------|
| Product Or Component Type | Selector switch |
| Device Short Name         | 9001SK          |
| Type Of Operator          | maintained      |

### Complementary

| Bezel Material                | Plastic                |
|-------------------------------|------------------------|
| Mounting Diameter             | 1.18 in (30 mm)        |
| Net Weight                    | 0.13 lb(US) (0.059 kg) |
| Shape Of Signaling Unit Head  | Round                  |
| Operator Position Information | 2 positions            |
| Contacts Type And Composition | Without contact block  |
| Mechanical Durability         | 500000 cycles          |
| Device Presentation           | Basic element          |

### Environment

| Protective Treatment                     | тс   |
|--|--|
| Ambient Air Temperature For<br>Storage   | -40158 °F (-4070 °C)   |
| Ambient Air Temperature For<br>Operation | -13158 °F (-2570 °C)   |
| Electrical Shock Protection Class        | Class II IEC 61140   |
| Ip Degree Of Protection                  | IP66 IEC 60529   |
| Nema Degree Of Protection                | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3<br>NEMA 4<br>NEMA 4<br>NEMA 6 |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Standards              | EN/IEC 60947-1<br>JIS C 4520<br>EN/IEC 60947-5-1<br>CSA C22.2 No 14<br>UL 508<br>EN/IEC 60947-5-4<br>JIS C 852 |
|------------------------|--|
| Product Certifications | NEMA<br>UL 508   |
| Vibration Resistance   | 7 gn 2500 Hz)IEC 60068-2-6   |
| Shock Resistance       | 50 gn IEC 60068-2-27   |

## Ordering and shipping details

| Category          | US10CS121429   |
|-------------------|----------------|
| Discount Schedule | 0CS1           |
| Gtin              | 00785901043638 |
| Returnability     | Yes            |
| Country Of Origin | MX             |

## **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

## Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

#### **Certifications & Standards**

| Reach Regulation          | REACh Declaration  |
|---------------------------|--|
| Eu Rohs Directive         | Pro-active compliance (Product out of EU RoHS legal scope)<br>EU RoHS Declaration  |
| China Rohs Regulation     | China RoHS declaration   |
| Environmental Disclosure  | Product Environmental Profile  |
| Weee                      | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.   |
| Circularity Profile       | No need of specific recycling operations   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |