



Overload Relay, Type S, melting alloy, replacement overload, NEMA sizes 00, 0, 1, 3 to 5 pole, 27A, 600VAC

9065SDO5

Product availability: Stock - Normally stocked in distribution facility

Price*: 152.00 USD

Main

Range Of Product	Replacement Relay
Product Destination	Starter
Thermal Overload Type	Melting alloy

Complementary

Nema Size	0 00 1
Phase	3 phase
Number Of Thermal Units Required	3
Mounting Support	Mounting plate
[Ue] Rated Operational Voltage	600 V AC
Height	4.00 in (101.6 mm)
Width	3.50 in (88.9 mm)
Depth	3.97 in (100.8 mm)

Ordering and shipping details

Category	US10CP121661
Discount Schedule	0CP1
Gtin	785901882312
Returnability	Yes
Country Of Origin	US

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.49 in (11.4 cm)
Package 1 Width	5.31 in (13.5 cm)
Package 1 Length	5.51 in (14.0 cm)
Package 1 Weight	15.20 oz (430.9 g)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Contractual warranty

Warranty

18 months

May 1, 2024

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive	Not compliant
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information.
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov