

Overload Relay, Type S, melting alloy, separate mount overload, NEMA size 3, 3 phase, 86A, 600VAC, isolated alarm contact

9065SEO12Y342

(!) Discontinued on: Oct 12, 2021

Main

Device Short Name	S
Product Or Component Type	Overload relay
Range Of Product	Type S
Thermal Overload Type	Melting alloy

Complementary

Depth	5.75 in (146.05 mm)
Height	5.59 in (141.99 mm)
Mounting Support	separate
Nema Size	3
Phase	3 phase
Number Of Thermal Units Required	3
Permissible Voltage	600 V AC 50/60 Hz
Product Destination	bottom 3 magnetic starter
Thermal Overload Class	Class 20
Width	5.31 in (134.87 mm)

Environment

Product Certifications	UL Listed
	CSA

Ordering and shipping details

Category	21661-9065 A,C,F,G,S(NOT SS)	
Discount Schedule	CP1	
Gtin	00785901433347	
Returnability	No	
Country Of Origin	MX	

Contractual warranty

14/		
Warranty	18 months	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

California Proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov