

# Terminal Block Class H Fuseholder 3 Pole 250V 60A

9080FB3221

#### Main

Range	9080FB
Product	Fuse holder

## Complementary

Current Rating	60 A
[Ue] Rated Operational Voltage	<= 250 V AC/DC
Fuse Type	
ruse Type	Н
Fuse Size	0.8125 x 3 in
Number Of Poles	3
Electrical Connection	Box lugs
Wire Gauge	AWG 14AWG 2 copper or aluminium
Sccr	10 kA UL 512
Product Certifications	UL listed file E40747 CCN IZLT CSA file 70360 class 6225 01 CE
Operating Temperature	-40257 °F (-40125 °C)
Mounting Type	Surface mount
Block Material	Thermoplastic: block
Wire Stripping Length	0.4375 in (11.11 mm)
Terminal Tightening Torque	lugs 25 lbf.in (2.82 N.m) AWG 14AWG 10 copper
Height	4.83 in (122.68 mm)
Width	4.23 in (107.44 mm)
Depth	2.01 in (51.05 mm)

## Ordering and shipping details

Category	21701-9080 FB
Discount Schedule	CP1
Gtin	00785901097082
Returnability	No
Country Of Origin	US

#### **Contractual warranty**

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Warranty

18 months

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov