

# Terminal Block Class H Fuseholder 3 Pole 250V 200A

9080FB3241

#### Main

Range	9080FB
Product	Fuse holder

### Complementary

Current Rating	200 A
[Ue] Rated Operational Voltage	<= 250 V AC/DC
Fuse Type	Н
Fuse Size	1.5 x 7.125 in
Number Of Poles	3
Electrical Connection	Box lugs
Wire Gauge	AWG 6250 kcmil copper or aluminium
Sccr	10 kA UL 512
Product Certifications	CSA file 70360 class 6225 01 UL listed file E40747 CCN IZLT
Operating Temperature	-40266 °F (-40130 °C)
Mounting Type	Surface mount
Block Material	Polyester: block
Wire Stripping Length	1.3125 in (33.34 mm)
Terminal Tightening Torque	lugs 275 lbf.in (31.07 N.m) AWG 6250 kcmil copper or aluminium
Height	9.63 in (244.60 mm)
Width	9 in (228.60 mm)
Depth	3.01 in (76.45 mm)

# Ordering and shipping details

Category	21701-9080 FB
Discount Schedule	CP1
Gtin	00785901097105
Returnability	No
Country Of Origin	US

### **Contractual warranty**

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Warranty

18 months

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov