Product data sheet

Specifications





servo motor BMH, Lexium 32, 65Nm, 3500rpm, untapped shaft, with brake, IP65, IP67, 128bit encoder, straight

BMH1903P21F2A

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 8,488.50 USD

Main

Product Or Component Type	Servo motor
Device Short Name	ВМН
Maximum Mechanical Speed	3500 rpm
Continuous Stall Torque	382.35 lbf.in (43.2 N.m) LXM32.D72N4 24 A, 400 V, three phase 382.35 lbf.in (43.2 N.m) LXM32.D72N4 24 A, 480 V, three phase 509.80 lbf.in (57.6 N.m) LXM32MD85N4 32 A, 400 V, three phase 509.80 lbf.in (57.6 N.m) LXM32MD85N4 32 A, 480 V, three phase 575.30 lbf.in (65 N.m) LXM32MC10N4 40 A, 400 V, three phase 575.30 lbf.in (65 N.m) LXM32MC10N4 40 A, 480 V, three phase
Peak Stall Torque	1086.87 lbf.in (122.8 N.m) LXM32.D72N4 24 A, 400 V, three phase 1086.87 lbf.in (122.8 N.m) LXM32.D72N4 24 A, 480 V, three phase 1250.61 lbf.in (141.3 N.m) LXM32MD85N4 32 A, 400 V, three phase 1250.61 lbf.in (141.3 N.m) LXM32MD85N4 32 A, 480 V, three phase 1440.01 lbf.in (162.7 N.m) LXM32MC10N4 40 A, 400 V, three phase 1440.01 lbf.in (162.7 N.m) LXM32MC10N4 40 A, 480 V, three phase
Nominal Output Power	5700 W LXM32.D72N4 24 A, 400 V, three phase 5700 W LXM32.D72N4 24 A, 480 V, three phase 7330 W LXM32MD85N4 32 A, 400 V, three phase 7330 W LXM32MD85N4 32 A, 480 V, three phase 7750 W LXM32MC10N4 40 A, 400 V, three phase 7750 W LXM32MC10N4 40 A, 480 V, three phase
Nominal Torque	318.63 lbf.in (36 N.m) LXM32.D72N4 24 A, 400 V, three phase 318.63 lbf.in (36 N.m) LXM32.D72N4 24 A, 480 V, three phase 309.78 lbf.in (35 N.m) LXM32MD85N4 32 A, 400 V, three phase 309.78 lbf.in (35 N.m) LXM32MD85N4 32 A, 480 V, three phase 327.48 lbf.in (37 N.m) LXM32MC10N4 40 A, 400 V, three phase 327.48 lbf.in (37 N.m) LXM32MC10N4 40 A, 480 V, three phase
Nominal Speed	1500 rpm LXM32.D72N4 24 A, 400 V, three phase 1500 rpm LXM32.D72N4 24 A, 480 V, three phase 2000 rpm LXM32MC10N4 40 A, 400 V, three phase 2000 rpm LXM32MC10N4 40 A, 480 V, three phase 2000 rpm LXM32MD85N4 32 A, 400 V, three phase 2000 rpm LXM32MD85N4 32 A, 480 V, three phase
Product Compatibility	LXM32.D72N4 400480 V three phase
Shaft End	Smooth shaft
Ip Degree Of Protection	IP65 standard IP67 with IP67 kit
Speed Feedback Resolution	131072 points/turn
Holding Brake	With
Mounting Support	International standard flange
Electrical Connection	Rotatable right-angled connectors

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Complementary

Lexium 32
Three phase
Continuous Stall Current 36.1 A Continuous Power 7.95 W Maximum Current Irms 72 A LXM32.D72N4 Maximum Permanent Current 124.5 A Second Shaft Without second shaft end Shaft Diameter 1.50 in (38 mm) Shaft Length 3.15 in (80 mm) Feedback Type Single turn Sin/Cos Hiperface Holding Torque 708.06 lbf.in (80 N.m) holding brake Motor Flange Size 7.48 in (190 mm) Number Of Motor Stacks 3 Torque Constant 1.8 N.m/A 248 °F (120 °C) Back Emf Constant 129.2 V/krpm 248 °F (120 °C) Number Of Motor Poles 10 Rotor Inertia 208.8 kg.cm² Stator Resistance 0.13 Ohm 68 °F (20 °C) Stator Inductance 3.62 mH 68 °F (20 °C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Continuous Power 7.95 W Maximum Current Irms 72 A LXM32.D72N4 Maximum Permanent Current 124.5 A Second Shaft Without second shaft end Shaft Diameter 1.50 in (38 mm) Shaft Length 3.15 in (80 mm) Feedback Type Single turn SinCos Hiperface Holding Torque 708.06 lbf.in (80 N.m) holding brake Motor Flange Size 7.48 in (190 mm) Number Of Motor Stacks 3 Torque Constant 1.8 N.m/A 248 "F (120 "C) Back Emf Constant 129.2 V/krpm 248 "F (120 "C) Number Of Motor Poles 10 Rotor Inertia 208.8 kg.cm² Stator Resistance 0.13 Ohm 68 "F (20 "C) Stator Inductance 3.62 mH 68 "F (20 "C) Stator Electrical Time Constant 27.8 ms 68 "F (20 "C) Maximum Axial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm) </th
Maximum Current Irms 72 A LXM32.D72N4 Maximum Permanent Current 124.5 A Second Shaft Without second shaft end Shaft Diameter 1.50 in (38 mm) Shaft Length 3.15 in (80 mm) Feedback Type Single turn SinCos Hiperface Holding Torque 708.06 lbf.in (80 N.m) holding brake Motor Flange Size 7.48 in (190 mm) Number Of Motor Stacks 3 Torque Constant 1.8 N.m/A 248 "F (120 "C) Back Emf Constant 129.2 V/krpm 248 "F (120 "C) Number Of Motor Poles 10 Rotor Inertia 208.8 kg.cm² Stator Resistance 0.13 Ohm 68 "F (20 "C) Stator Inductance 3.62 mH 68 "F (20 "C) Stator Electrical Time Constant 27.8 ms 68 "F (20 "C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Maximum Permanent Current 124.5 A Second Shaft Without second shaft end Shaft Diameter 1.50 in (38 mm) Shaft Length 3.15 in (80 mm) Feedback Type Single turn SinCos Hiperface Holding Torque 708.06 lbf.in (80 N.m) holding brake Motor Flange Size 7.48 in (190 mm) Number Of Motor Stacks 3 Torque Constant 1.8 N.m/A 248 "F (120 "C) Back Emf Constant 129.2 V/krpm 248 "F (120 "C) Number Of Motor Poles 10 Rotor Inertia 208.8 kg.cm" Stator Resistance 0.13 Ohm 68 "F (20 "C) Stator Inductance 3.62 mH 68 "F (20 "C) Stator Electrical Time Constant 27.8 ms 68 "F (20 "C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Second Shaft Without second shaft end 1.50 in (38 mm) Shaft Diameter 1.50 in (38 mm) Shaft Length 3.15 in (80 mm) Feedback Type Single turn SinCos Hiperface Motor Flange Size 7.48 in (190 mm) Number Of Motor Stacks 3 Torque Constant 1.8 N.m/A 248 °F (120 °C) Back Emf Constant 129.2 V/krpm 248 °F (120 °C) Number Of Motor Poles 10 Rotor Inertia 208.8 kg.cm² Stator Resistance 0.13 Ohm 68 °F (20 °C) Stator Inductance 3.62 mH 68 °F (20 °C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Shaft Length 3.15 in (38 mm)
Shaft Length 3.15 in (80 mm)
Feedback Type Single turn SinCos Hiperface 708.06 lbf.in (80 N.m) holding brake Motor Flange Size 7.48 in (190 mm) Number Of Motor Stacks 3 Torque Constant 1.8 N.m/A 248 °F (120 °C) Back Emf Constant 129.2 V/krpm 248 °F (120 °C) Number Of Motor Poles 10 Rotor Inertia 208.8 kg.cm² Stator Resistance 0.13 Ohm 68 °F (20 °C) Stator Inductance 3.62 mH 68 °F (20 °C) Stator Electrical Time Constant 27.8 ms 68 °F (20 °C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
##
Motor Flange Size 7.48 in (190 mm) Number Of Motor Stacks 3 Torque Constant 1.8 N.m/A 248 °F (120 °C) Back Emf Constant 129.2 V/krpm 248 °F (120 °C) Number Of Motor Poles 10 Rotor Inertia 208.8 kg.cm² Stator Resistance 0.13 Ohm 68 °F (20 °C) Stator Inductance 3.62 mH 68 °F (20 °C) Stator Electrical Time Constant 27.8 ms 68 °F (20 °C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-in Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Number Of Motor Stacks 3 Torque Constant 1.8 N.m/A 248 °F (120 °C) Back Emf Constant 129.2 V/krpm 248 °F (120 °C) Number Of Motor Poles 10 Rotor Inertia 208.8 kg.cm² Stator Resistance 0.13 Ohm 68 °F (20 °C) Stator Inductance 3.62 mH 68 °F (20 °C) Stator Electrical Time Constant 27.8 ms 68 °F (20 °C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Torque Constant 1.8 N.m/A 248 °F (120 °C) Back Emf Constant 129.2 V/krpm 248 °F (120 °C) Number Of Motor Poles 10 Rotor Inertia 208.8 kg.cm² Stator Resistance 0.13 Ohm 68 °F (20 °C) Stator Inductance 3.62 mH 68 °F (20 °C) Stator Electrical Time Constant 27.8 ms 68 °F (20 °C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Back Emf Constant 129.2 V/krpm 248 °F (120 °C) Number Of Motor Poles 10 Rotor Inertia 208.8 kg.cm² Stator Resistance 0.13 Ohm 68 °F (20 °C) Stator Inductance 3.62 mH 68 °F (20 °C) Stator Electrical Time Constant 27.8 ms 68 °F (20 °C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Number Of Motor Poles 10 Rotor Inertia 208.8 kg.cm² Stator Resistance 0.13 Ohm 68 °F (20 °C) Stator Inductance 3.62 mH 68 °F (20 °C) Stator Electrical Time Constant 27.8 ms 68 °F (20 °C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Rotor Inertia 208.8 kg.cm² Stator Resistance 0.13 Ohm 68 °F (20 °C) Stator Inductance 3.62 mH 68 °F (20 °C) Stator Electrical Time Constant 27.8 ms 68 °F (20 °C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Stator Resistance 0.13 Ohm 68 °F (20 °C) Stator Inductance 3.62 mH 68 °F (20 °C) Stator Electrical Time Constant 27.8 ms 68 °F (20 °C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Stator Inductance 3.62 mH 68 °F (20 °C) Stator Electrical Time Constant 27.8 ms 68 °F (20 °C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Stator Electrical Time Constant 27.8 ms 68 °F (20 °C) Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Maximum Radial Force Fr 4500 N 1000 rpm Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Maximum Axial Force Fa 0.2 x Fr Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Brake Pull-In Power 40 W Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Type Of Cooling Natural convection Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Length 14.57 in (370 mm) Centring Collar Diameter 7.09 in (180 mm)
Centring Collar Diameter 7.09 in (180 mm)
Centring Collar Depth 0 16 in (4 mm)
Number Of Mounting Holes 4
Mounting Holes Diameter 0.55 in (14 mm)
Circle Diameter Of The Mounting 8.46 in (215 mm) Holes

Ordering and shipping details

Category	US1PC5318282
Discount Schedule	PC53
Gtin	3606485264288
Returnability	No
Country Of Origin	DE

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.81 in (30.0 cm)
Package 1 Width	15.75 in (40.0 cm)
Package 1 Length	31.30 in (79.5 cm)
Package 1 Weight	69.45 lb(US) (31.5 kg)

Contractual warranty

Apr 24, 2024

Warranty 18 months

Sustainability Green Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov