Product data sheet

Specifications





servo motor BMH, Lexium 32, 34.4Nm, 3800rpm, untapped shaft, without brake, IP54, 16bit encoder, straight

BMH2051P06A1A

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 4,095.00 USD

Main

Servo motor	
ВМН	
3800 rpm	
304.47 lbf.in (34.4 N.m) LXM32.D72N4 24 A, 400 V, three phase 304.47 lbf.in (34.4 N.m) LXM32.D72N4 24 A, 480 V, three phase	
915.17 lbf.in (103.4 N.m) LXM32.D72N4 24 A, 400 V, three phase 915.17 lbf.in (103.4 N.m) LXM32.D72N4 24 A, 480 V, three phase	
5400 W LXM32.D72N4 24 A, 400 V, three phase 5400 W LXM32.D72N4 24 A, 480 V, three phase	
228.35 lbf.in (25.8 N.m) LXM32.D72N4 24 A, 400 V, three phase 228.35 lbf.in (25.8 N.m) LXM32.D72N4 24 A, 480 V, three phase	
2000 rpm LXM32.D72N4 24 A, 400 V, three phase 2000 rpm LXM32.D72N4 24 A, 480 V, three phase	
LXM32.D72N4 400480 V three phase	
Smooth shaft	
IP54 standard	
32768 points/turn	
Without	
International standard flange	
Straight connectors	

Complementary

Range Compatibility	Lexium 32
[Us] Rated Supply Voltage	480 V
Phase	Three phase
Continuous Stall Current	21.5 A
Continuous Power	6.8 W
Maximum Current Irms	72 A LXM32.D72N4
Maximum Permanent Current	78.1 A
Second Shaft	Without second shaft end
Shaft Diameter	1.50 in (38 mm)

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Shaft Length3.15 in (80 mm)Feedback TypeSingle turn SinCos HiperfaceMotor Flange Size8.07 in (205 mm)Number Of Motor Stacks1Back Emf Constant104 V/krpm 248 °F (120 °C)Number Of Motor Poles10Rotor Inertia71.4 kg.cm²Stator Resistance0.3 Ohm 68 °F (20 °C)Stator Resistance5.9 mH 68 °F (20 °C)Stator Electrical Time Constant19.7 ms 68 °F (20 °C)Maximum Radial Force Fr3730 N 1000 rpm 2560 N 2000 rpm 2580 N 3000 rpmZastor Inductance0.2 x FrType Of CoolingNatural convectionLength12.64 in (321 mm)Centring Collar Diameter7.09 in (180 mm)Centring Collar Depth0.16 in (4 mm)Number Of Mounting Holes4Mounting Holes Diameter0.55 in (14 mm)Circle Diameter Of The Mounting 8.46 in (215 mm)		
Motor Flange Size8.07 in (205 mm)Number Of Motor Stacks1Back Emf Constant104 V/krpm 248 °F (120 °C)Number Of Motor Poles10Rotor Inertia71.4 kg.cm²Stator Resistance0.3 Ohm 68 °F (20 °C)Stator Inductance5.9 mH 68 °F (20 °C)Stator Electrical Time Constant19.7 ms 68 °F (20 °C)Maximum Radial Force Fr3730 N 1000 rpm 2560 N 2000 rpm 2560 N 3000 rpmMaximum Axial Force Fa0.2 x FrType Of CoolingNatural convectionLength12.64 in (321 mm)Centring Collar Diameter7.09 in (180 mm)Centring Collar Depth0.16 in (4 mm)Number Of Mounting Holes4Mounting Holes Diameter0.55 in (14 mm)Circle Diameter Of The Mounting8.46 in (215 mm)	haft Length	3.15 in (80 mm)
Number Of Motor Stacks 1 Back Emf Constant 104 V/krpm 248 °F (120 °C) Number Of Motor Poles 10 Rotor Inertia 71.4 kg.cm² Stator Resistance 0.3 Ohm 68 °F (20 °C) Stator Inductance 5.9 mH 68 °F (20 °C) Stator Electrical Time Constant 19.7 ms 68 °F (20 °C) Maximum Radial Force Fr 3730 N 1000 rpm 2560 N 2000 rpm 2560 N 3000 rpm 2560 N 3000 rpm 266 N 2000 rpm 2560 N 3000 rpm 2580 N 3000 rpm 2560 N 3000 rpm 2560 N 3000 rpm 2560 N 3000 rpm Maximum Axial Force Fa 0.2 x Fr Type Of Cooling Natural convection Length 12.64 in (321 mm) Centring Collar Diameter 7.09 in (180 mm) Centring Collar Depth 0.16 in (4 mm) Number Of Mounting Holes 4 Mounting Holes Diameter 0.55 in (14 mm) Circle Diameter Of The Mounting 8.46 in (215 mm)	eedback Type	Single turn SinCos Hiperface
Back Emf Constant 104 V/krpm 248 °F (120 °C) Number Of Motor Poles 10 Rotor Inertia 71.4 kg.cm² Stator Resistance 0.3 Ohm 68 °F (20 °C) Stator Inductance 5.9 mH 68 °F (20 °C) Stator Electrical Time Constant 19.7 ms 68 °F (20 °C) Maximum Radial Force Fr 3730 N 1000 rpm 2960 N 2000 rpm 2580 N 3000 rpm Maximum Axial Force Fa 0.2 x Fr Type Of Cooling Natural convection Length 12.64 in (321 mm) Centring Collar Diameter 7.09 in (180 mm) Centring Collar Depth 0.16 in (4 mm) Number Of Mounting Holes 4 Mounting Holes Diameter 0.55 in (14 mm) Circle Diameter Of The Mounting 8.46 in (215 mm)	lotor Flange Size	8.07 in (205 mm)
Number Of Motor Poles10Rotor Inertia71.4 kg.cm²Stator Resistance0.3 Ohm 68 °F (20 °C)Stator Inductance5.9 mH 68 °F (20 °C)Stator Electrical Time Constant19.7 ms 68 °F (20 °C)Maximum Radial Force Fr3730 N 1000 rpm 2960 N 2000 rpm 2580 N 3000 rpmMaximum Axial Force Fa0.2 x FrType Of CoolingNatural convectionLength12.64 in (321 mm)Centring Collar Diameter7.09 in (180 mm)Centring Collar Depth0.16 in (4 mm)Number Of Mounting Holes4Mounting Holes Diameter0.55 in (14 mm)Circle Diameter Of The Mounting8.46 in (215 mm)	lumber Of Motor Stacks	1
Rotor Inertia71.4 kg.cm²Stator Resistance0.3 Ohm 68 °F (20 °C)Stator Inductance5.9 mH 68 °F (20 °C)Stator Electrical Time Constant19.7 ms 68 °F (20 °C)Maximum Radial Force Fr3730 N 1000 rpm 2960 N 2000 rpm 2580 N 3000 rpmMaximum Axial Force Fa0.2 x FrType Of CoolingNatural convectionLength12.64 in (321 mm)Centring Collar Diameter7.09 in (180 mm)Centring Collar Depth0.16 in (4 mm)Number Of Mounting Holes4Mounting Holes Diameter0.55 in (14 mm)Circle Diameter Of The Mounting8.46 in (215 mm)	ack Emf Constant	104 V/krpm 248 °F (120 °C)
Stator Resistance 0.3 Ohm 68 °F (20 °C) Stator Inductance 5.9 mH 68 °F (20 °C) Stator Electrical Time Constant 19.7 ms 68 °F (20 °C) Maximum Radial Force Fr 3730 N 1000 rpm 2960 N 2000 rpm 2580 N 3000 rpm Maximum Axial Force Fa 0.2 x Fr Type Of Cooling Natural convection Length 12.64 in (321 mm) Centring Collar Diameter 7.09 in (180 mm) Centring Collar Depth 0.16 in (4 mm) Number Of Mounting Holes 4 Mounting Holes Diameter 0.55 in (14 mm) Circle Diameter Of The Mounting 8.46 in (215 mm)	lumber Of Motor Poles	10
Stator Inductance5.9 mH 68 °F (20 °C)Stator Electrical Time Constant19.7 ms 68 °F (20 °C)Maximum Radial Force Fr3730 N 1000 rpm 2960 N 2000 rpm 2580 N 3000 rpmMaximum Axial Force Fa0.2 x FrType Of CoolingNatural convectionLength12.64 in (321 mm)Centring Collar Diameter7.09 in (180 mm)Centring Collar Depth0.16 in (4 mm)Number Of Mounting Holes4Mounting Holes Diameter0.55 in (14 mm)Circle Diameter Of The Mounting8.46 in (215 mm)	otor Inertia	71.4 kg.cm ²
Stator Electrical Time Constant 19.7 ms 68 °F (20 °C) Maximum Radial Force Fr 3730 N 1000 rpm 2960 N 2000 rpm 2580 N 3000 rpm Maximum Axial Force Fa 0.2 x Fr Type Of Cooling Natural convection Length 12.64 in (321 mm) Centring Collar Diameter 7.09 in (180 mm) Centring Collar Depth 0.16 in (4 mm) Number Of Mounting Holes 4 Mounting Holes Diameter 0.55 in (14 mm) Circle Diameter Of The Mounting 8.46 in (215 mm)	tator Resistance	0.3 Ohm 68 °F (20 °C)
Maximum Radial Force Fr3730 N 1000 rpm 2960 N 2000 rpm 2580 N 3000 rpmMaximum Axial Force Fa0.2 x FrType Of CoolingNatural convectionLength12.64 in (321 mm)Centring Collar Diameter7.09 in (180 mm)Centring Collar Depth0.16 in (4 mm)Number Of Mounting Holes4Mounting Holes Diameter0.55 in (14 mm)Circle Diameter Of The Mounting8.46 in (215 mm)	tator Inductance	5.9 mH 68 °F (20 °C)
Animum Axial Force Fa 0.2 x Fr Type Of Cooling Natural convection Length 12.64 in (321 mm) Centring Collar Diameter 7.09 in (180 mm) Centring Collar Depth 0.16 in (4 mm) Number Of Mounting Holes 4 Mounting Holes Diameter 0.55 in (14 mm) Circle Diameter Of The Mounting 8.46 in (215 mm)	tator Electrical Time Constant	19.7 ms 68 °F (20 °C)
Type Of Cooling Natural convection Length 12.64 in (321 mm) Centring Collar Diameter 7.09 in (180 mm) Centring Collar Depth 0.16 in (4 mm) Number Of Mounting Holes 4 Mounting Holes Diameter 0.55 in (14 mm) Circle Diameter Of The Mounting 8.46 in (215 mm)		2960 N 2000 rpm
Length 12.64 in (321 mm) Centring Collar Diameter 7.09 in (180 mm) Centring Collar Depth 0.16 in (4 mm) Number Of Mounting Holes 4 Mounting Holes Diameter 0.55 in (14 mm) Circle Diameter Of The Mounting 8.46 in (215 mm)	laximum Axial Force Fa	0.2 x Fr
Centring Collar Diameter 7.09 in (180 mm) Centring Collar Depth 0.16 in (4 mm) Number Of Mounting Holes 4 Mounting Holes Diameter 0.55 in (14 mm) Circle Diameter Of The Mounting 8.46 in (215 mm)	ype Of Cooling	Natural convection
Centring Collar Depth 0.16 in (4 mm) Number Of Mounting Holes 4 Mounting Holes Diameter 0.55 in (14 mm) Circle Diameter Of The Mounting 8.46 in (215 mm)	ength	12.64 in (321 mm)
Number Of Mounting Holes 4 Mounting Holes Diameter 0.55 in (14 mm) Circle Diameter Of The Mounting 8.46 in (215 mm)	entring Collar Diameter	7.09 in (180 mm)
Mounting Holes Diameter 0.55 in (14 mm) Circle Diameter Of The Mounting 8.46 in (215 mm)	entring Collar Depth	0.16 in (4 mm)
Circle Diameter Of The Mounting 8.46 in (215 mm)	lumber Of Mounting Holes	4
	lounting Holes Diameter	0.55 in (14 mm)
	Fircle Diameter Of The Mounting loles	8.46 in (215 mm)
Net Weight 72.75 lb(US) (33 kg)	let Weight	72.75 lb(US) (33 kg)

Ordering and shipping details

Category	US1PC5318282	
Discount Schedule	PC53	
Gtin	3606485202723	
Returnability	No	
Country Of Origin	DE	

Packing Units

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	14.17 in (36.0 cm)	
Package 1 Width	12.20 in (31.0 cm)	
Package 1 Length	22.83 in (58.0 cm)	
Package 1 Weight	85.98 lb(US) (39.0 kg)	

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov