# **Product data sheet**

Specification





servo motor BMH, Lexium 32, 62.5Nm, 3800rpm, untapped shaft, with brake, IP65, IP67, 16bit encoder, straight

BMH2052P26F1A

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 9,825.00 USD

#### Main

Product Or Component Type	Servo motor
Device Short Name	ВМН
Maximum Mechanical Speed	3800 rpm
Continuous Stall Torque	553.17 lbf.in (62.5 N.m) LXM32.D72N4 24 A, 400 V, three phase 553.17 lbf.in (62.5 N.m) LXM32.D72N4 24 A, 480 V, three phase
Peak Stall Torque	1504.62 lbf.in (170 N.m) LXM32.D72N4 24 A, 400 V, three phase 1504.62 lbf.in (170 N.m) LXM32.D72N4 24 A, 480 V, three phase
Nominal Output Power	6500 W LXM32.D72N4 24 A, 400 V, three phase 6500 W LXM32.D72N4 24 A, 480 V, three phase
Nominal Torque	368.19 lbf.in (41.6 N.m) LXM32.D72N4 24 A, 400 V, three phase 368.19 lbf.in (41.6 N.m) LXM32.D72N4 24 A, 480 V, three phase
Nominal Speed	1500 rpm LXM32.D72N4 24 A, 400 V, three phase 1500 rpm LXM32.D72N4 24 A, 480 V, three phase
Product Compatibility	LXM32.D72N4 400480 V three phase
Shaft End	Smooth shaft
Ip Degree Of Protection	IP65 standard IP67 with IP67 kit
Speed Feedback Resolution	32768 points/turn
Holding Brake	With
Mounting Support	International standard flange
Electrical Connection	Straight connectors

#### Complementary

Range Compatibility	Lexium 32
[Us] Rated Supply Voltage	480 V
Phase	Three phase
Continuous Stall Current	24.2 A
Continuous Power	7.85 W
Maximum Current Irms	72 A LXM32.D72N4
Maximum Permanent Current	96.8 A
Second Shaft	Without second shaft end
Shaft Diameter	1.50 in (38 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Shaft Length	3.15 in (80 mm)
Feedback Type	Single turn SinCos Hiperface
Holding Torque	708.06 lbf.in (80 N.m) holding brake
Motor Flange Size	8.07 in (205 mm)
Number Of Motor Stacks	2
Torque Constant	2.6 N.m/A 248 °F (120 °C)
Back Emf Constant	161 V/krpm 248 °F (120 °C)
Number Of Motor Poles	10
Rotor Inertia	145 kg.cm²
Stator Resistance	0.3 Ohm 68 °F (20 °C)
Stator Inductance	5.6 mH 68 °F (20 °C)
Stator Electrical Time Constant	18.7 ms 68 °F (20 °C)
Maximum Radial Force Fr	4200 N 1000 rpm 3330 N 2000 rpm 2910 N 3000 rpm
Maximum Radial Force Fr  Maximum Axial Force Fa	3330 N 2000 rpm
	3330 N 2000 rpm 2910 N 3000 rpm
Maximum Axial Force Fa	3330 N 2000 rpm 2910 N 3000 rpm 0.2 x Fr
Maximum Axial Force Fa Brake Pull-In Power	3330 N 2000 rpm 2910 N 3000 rpm 0.2 x Fr 40 W
Maximum Axial Force Fa Brake Pull-In Power Type Of Cooling	3330 N 2000 rpm 2910 N 3000 rpm 0.2 x Fr 40 W Natural convection
Maximum Axial Force Fa  Brake Pull-In Power  Type Of Cooling  Length	3330 N 2000 rpm 2910 N 3000 rpm 0.2 x Fr 40 W Natural convection 17.89 in (454.5 mm)
Maximum Axial Force Fa  Brake Pull-In Power  Type Of Cooling  Length  Centring Collar Diameter	3330 N 2000 rpm 2910 N 3000 rpm 0.2 x Fr 40 W Natural convection 17.89 in (454.5 mm) 7.09 in (180 mm)
Maximum Axial Force Fa  Brake Pull-In Power  Type Of Cooling  Length  Centring Collar Diameter  Centring Collar Depth	3330 N 2000 rpm 2910 N 3000 rpm  0.2 x Fr  40 W  Natural convection  17.89 in (454.5 mm)  7.09 in (180 mm)  0.16 in (4 mm)
Maximum Axial Force Fa  Brake Pull-In Power  Type Of Cooling  Length  Centring Collar Diameter  Centring Collar Depth  Number Of Mounting Holes	3330 N 2000 rpm 2910 N 3000 rpm  0.2 x Fr  40 W  Natural convection  17.89 in (454.5 mm)  7.09 in (180 mm)  0.16 in (4 mm)

# Ordering and shipping details

Category	US1PC5318282
Discount Schedule	PC53
Gtin	3606485203263
Returnability	No
Country Of Origin	DE

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	14.17 in (36.0 cm)
Package 1 Width	12.20 in (31.0 cm)
Package 1 Length	28.74 in (73.0 cm)
Package 1 Weight	127.87 lb(US) (58.0 kg)

# **Contractual warranty**

Warranty

May 1, 2024

18 months

### Sustainability Green Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>②</b>	Mercury Free	
	Rohs Exemption Information	Yes
<b>⊘</b>	Pvc Free	

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov