# **Product data sheet**

Specifications





Motor Circuit Protector, TeSys BV4, standard fault, 25A, 600Y/ 347 VAC, 110 to 360 instantaneous trip, up to 100kA SCCR

BV4T025D

Product availability: Stock - Normally stocked in distribution facility

Price\*: 400.00 USD

#### Main

| Panga                     | T-0                     |
|---------------------------|-------------------------|
| Range                     | TeSys                   |
| Product Name              | TeSys BV4               |
| Device Short Name         | BV4                     |
| Product Or Component Type | Motor Circuit Protector |
| Device Application        | Motor                   |
| Performance Level         | Standard                |
| Poles Description         | 3P                      |
| Utilisation Category      | Category A              |
| Trip Unit Technology      | Magnetic                |
| Protection Type           | Short-circuit           |
| Line Rated Current        | 25 A 104 °F (40 °C)     |
| Magnetic Setting Range    | 110360 A 104 °F (40 °C) |
| Control Type              | Toggle                  |

### Complementary

| [Ue] Rated Operational Voltage | 600Y/347 V AC 50/60 Hz                                |
|--------------------------------|---|
| Mounting Mode                  | By screws   |
|                                | By clips  |
| Mounting Support               | 75 mm symmetrical DIN rail                            |
|                                | Plate   |
|                                | 35 mm symmetrical DIN rail                            |
| Mechanical Durability          | 40000 cycles  |
| Electrical Durability          | 40000 cycles AC-3 440 V In/2                          |
|                                | 20000 cycles AC-3 440 V In                            |
| Local Signalling               | for presence of auxiliary contacts flag (green)       |
| Number Of Slots                | 1 alarm switch fault signalling contact, plug-in      |
|                                | 1 voltage release electrical remote tripping, plug-in |
|                                | 1 auxiliary switch open/close contact, plug-in        |
| Connection Pitch               | 1.06 in (27 mm)                                       |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Electrical Connection | 2 EverLink BTR screw connectors 0.000.11 in² (1.570 mm²) AWG 14AWG 2/0), solid copper 2 EverLink BTR screw connectors 0.000.08 in² (1.550 mm²) AWG 6AWG 1/0), flexible copper |
|-----------------------|---|
| Tightening Torque     | 44.25 lbf.in (5 N.m) 0.02 in² (10 mm²) (AWG 8)<br>79.66 lbf.in (9 N.m) 0.02 in² (16 mm²) (AWG 6)  |
| Wire Stripping Length | 0.79 in (20 mm)   |
| Height                | 6.38 in (162 mm)  |
| Width                 | 3.19 in (81 mm)   |
| Depth                 | 4.57 in (116 mm)  |
| Net Weight            | 3.31 lb(US) (1.5 kg)  |
| Quantity Per Set      | 1   |
| Color                 | Gray RAL 7016)  |

### **Environment**

| Standards                             | UL 489<br>CSA C22.2 No 5  |
|---------------------------------------|---|
| Product Certifications                | CSA<br>UL   |
| Ip Degree Of Protection               | IP40 front face IEC 60529   |
| Ik Degree Of Protection               | IK07 conforming to IEC 62262  |
| Mechanical Robustness                 | Vibrations +/- 1 mm 213.2 Hz IEC 60068-2-6<br>Vibrations 0.7 gn 13.2100 Hz IEC 60068-2-6<br>Shocks 15 gn 11 ms IEC 60068-2-27 |
| Ambient Air Temperature For Operation | -13158 °F (-2570 °C)  |
| Ambient Air Temperature For Storage   | -58185 °F (-5085 °C)  |
| Operating Altitude                    | 6561.68 ft (2000 m) without derating > 20005000 m with derating   |

# Ordering and shipping details

| Category          | US10l1101124  |  |
|-------------------|---------------|--|
| Discount Schedule | 0111          |  |
| Gtin              | 3606481328335 |  |
| Returnability     | Yes           |  |
| Country Of Origin | MX            |  |

### **Packing Units**

| Unit Type Of Package 1       | PCE                   |
|------------------------------|-----------------------|
| Number Of Units In Package 1 | 1                     |
| Package 1 Height             | 4.30 in (10.92 cm)    |
| Package 1 Width              | 6.50 in (16.51 cm)    |
| Package 1 Length             | 8.70 in (22.1 cm)     |
| Package 1 Weight             | 3.90 lb(US) (1.77 kg) |



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

| <b>Ø</b> | Mercury Free                       |
|----------|------------------------------------|
| <b>Ø</b> | Rohs Exemption Information Yes     |
| <b>Ø</b> | Pvc Free                           |
| <b>Ø</b> | Halogen Free Plastic Parts Product |

### **Certifications & Standards**

| Reach Regulation         | REACh Declaration  |
|--------------------------|--|
| Eu Rohs Directive        | Compliant with Exemptions  |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.                         |
| Environmental Disclosure | Product Environmental Profile  |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile      | End of Life Information  |