Product data sheet

Specification





TeSys F magnetic latching contactor - 3P(3 NO) - 400 A - 220...230 V AC/DC coil

CR1F400M7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 2,217.00 USD

Main

Range	TeSys
Product Name	TeSys F
Product Or Component Type	Magnetic latching contactor
Device Short Name	CR1F
Device Application	Control
Contactor Application	Motor control Resistive load
Utilisation Category	AC-1 AC-3 AC-4
Poles Description	3P
Power Pole Contact Composition	3 NO
[Ue] Rated Operational Voltage	1000 V AC 25200 Hz
[le] Rated Operational Current	400 A (at <104 °F (40 °C)) at <= 440 V AC AC-3 500 A (at <104 °F (40 °C)) at <= 440 V AC AC-1 370 A (at <104 °F (40 °C)) at <= 440 V AC AC-4
Motor Power Kw	200 kW at 400 V AC 50/60 Hz (AC-4)
Control Circuit Type	AC 50400 Hz DC standard
[Uc] Control Circuit Voltage	220230 V AC 50400 Hz 220230 V DC
Irms Rated Making Capacity	4500 A
Rated Breaking Capacity	4000 A at 220440 V 3500 A at 500 V 1200 A at 1000 V 3000 A at 660/690 V
[Icw] Rated Short-Time Withstand Current	3600 A 104 °F (40 °C) - 1 s 3600 A 104 °F (40 °C) - 5 s 3600 A 104 °F (40 °C) - 10 s 2400 A 104 °F (40 °C) - 30 s 1700 A 104 °F (40 °C) - 3 min 1200 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	400 A aM at <= 440 V 500 A BS88 at <= 440 V 500 A gG at <= 440 V
Average Impedance	0.28 mOhm - Ith 500 A 50 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

[Ui] Rated Insulation Voltage	1000 V IEC 60158-1 1000 V IEC 60947-4 1000 V BS 775 1500 V VDE 0110 group C
Power Dissipation Per Pole	45 W AC-3 70 W AC-1
Standards	EN/IEC 60947-1 EN/IEC 60947-4-1 JIS C8201-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product Certifications	CB Scheme UL CSA EAC CE UKCA
Connections - Terminals	lugs-ring terminals 2 0.23 in² (150 mm²) bars 2 30 x 5 mm Power circuit bolted connection
Tightening Torque	309.78 lbf.in (35 N.m)
Operating Time	4075 ms latching 50100 ms unlatching
Mechanical Durability	1 Mcycles
Maximum Operating Rate	120 cyc/h 104 °F (40 °C)

Complementary

Control Circuit Voltage Limits	Latching: 0.851.1 Uc Unlatching: 0.851.1 Uc
Average Consumption	1600 VA AC 50400 Hz latching 16 VA AC 50400 Hz unlatching 1600 VA DC latching 16 VA DC unlatching

Environment

Protective Treatment	TC
Ambient Air Temperature For Operation	5158 °F (-1570 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Operating Altitude	9842.52 ft (3000 m) without derating
Height	8.11 in (206 mm)
Width	8.39 in (213 mm)
Depth	8.62 in (219 mm)
Net Weight	20.06 lb(US) (9.1 kg)

Ordering and shipping details

Category	US10I1222336
Discount Schedule	0112
Gtin	3389110548556
Returnability	No
Country Of Origin	US

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.84 in (25.000 cm)
Package 1 Width	10.24 in (26.000 cm)
Package 1 Length	11.81 in (30.000 cm)
Package 1 Weight	20.06 lb(US) (9.101 kg)
Unit Type Of Package 2	P06
Number Of Units In Package 2	8
Package 2 Height	29.53 in (75.000 cm)
Package 2 Width	31.50 in (80.000 cm)
Package 2 Length	23.62 in (60.000 cm)
Package 2 Weight	185.56 lb(US) (84.168 kg)

Contractual warranty

Warranty 18 months

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Circularity Profile	End of Life Information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Environmental Disclosure	Product Environmental Profile
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Eu Rohs Directive	Compliant with Exemptions
Reach Regulation	REACh Declaration