Product data sheet

Specifications





Magnetic latching contactor,TeSys F,3P(3NO),AC-3 <=440V 630A, 220-230V DC coil

CR1F630M7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 10,715.00 USD

Main

tching contactor
ad ol
25200 Hz
104 °F (40 °C)) at <= 440 V AC AC-3 <104 °F (40 °C)) at <= 440 V AC AC-1 104 °F (40 °C)) at <= 440 V AC AC-4
100 V AC 50/60 Hz (AC-4)
) Hz d
AC 50400 Hz DC
20440 V 00 V 000 V 60/690 V
I °F (40 °C) - 1 s I °F (40 °C) - 5 s I °F (40 °C) - 10 s °F (40 °C) - 30 s °F (40 °C) - 1 min °F (40 °C) - 3 min °F (40 °C) - 10 min
t <= 440 V 88 at <= 440 V at <= 440 V
- Ith 1000 A 50 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

[Ui] Rated Insulation Voltage	1000 V IEC 60158-1
	1000 V IEC 60947-4
	1000 V BS 775
	1500 V VDE 0110 group C
Power Dissipation Per Pole	48 W AC-3
·	120 W AC-1
Standards	EN/IEC 60947-1
	EN/IEC 60947-4-1
	JIS C8201-4-1
	UL 60947-4-1
	CSA C22.2 No 60947-4-1
Product Certifications	CB Scheme
	UL
	CSA
	EAC
	CE
	UKCA
Connections - Terminals	bars 2 60 x 5 mm
	Power circuit bolted connection
Tightening Torque	513.34 lbf.in (58 N.m)
Operating Time	4080 ms latching
	50100 ms unlatching
Mechanical Durability	1 Mcycles
Maximum Operating Rate	120 cyc/h 104 °F (40 °C)
	-

Complementary

Control Circuit Voltage Limits	Latching: 0.851.1 Uc Unlatching: 0.851.1 Uc
Average Consumption	11 VA AC 50400 Hz unlatching 2300 VA AC 50400 Hz latching 11 VA DC unlatching 2300 VA DC latching

Environment

Protective Treatment	TC
Ambient Air Temperature For Operation	5158 °F (-1570 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Operating Altitude	9842.52 ft (3000 m) without derating
Height	11.97 in (304 mm)
Width	12.17 in (309 mm)
Depth	10.04 in (255 mm)
Net Weight	41.01 lb(US) (18.6 kg)

Ordering and shipping details

Category	US10I1222331
Discount Schedule	0112
Gtin	3389110548907
Returnability	No
Country Of Origin	US

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.83 in (27.5 cm)
Package 1 Width	13.39 in (34.0 cm)
Package 1 Length	13.78 in (35.0 cm)
Package 1 Weight	36.09 lb(US) (16.37 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Circularity Profile	End of Life Information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Environmental Disclosure	Product Environmental Profile
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Eu Rohs Directive	Compliant with Exemptions
Reach Regulation	REACh Declaration