Product data sheet

Specifications





Magnetic latching contactor,TeSys F,3P(3NO),AC-3 <=440V 630A, 220V DC coil with low inrush consumption

CR1F630MZ7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 10,480.00 USD

Main

| Range | TeSys | |
|---|---|--|
| Product Name | TeSys F | |
| Product Or Component Type | Magnetic latching contactor | |
| Device Short Name | CR1F | |
| Device Application | Control | |
| Contactor Application | Resistive load Motor control | |
| Utilisation Category | AC-4 AC-1 AC-3 | |
| Poles Description | 3P | |
| Power Pole Contact Composition | 3 NO | |
| [Ue] Rated Operational Voltage | 1000 V AC 25200 Hz | |
| [le] Rated Operational Current | 630 A (at <104 °F (40 °C)) at <= 440 V AC AC-3 1000 A (at <104 °F (40 °C)) at <= 440 V AC AC-1 560 A (at <104 °F (40 °C)) at <= 440 V AC AC-4 | |
| Motor Power Kw | 335 kW at 400 V AC 50/60 Hz (AC-4) | |
| Control Circuit Type | DC low consumption | |
| [Uc] Control Circuit Voltage 220 V DC | | |
| Irms Rated Making Capacity | 6740 A | |
| Rated Breaking Capacity | 6300 A at 220440 V 5400 A at 500 V 3200 A at 1000 V 4600 A at 660/690 V | |
| [Icw] Rated Short-Time Withstand Current | 5.05 kA 104 °F (40 °C) - 1 s 5.05 kA 104 °F (40 °C) - 5 s 5.05 kA 104 °F (40 °C) - 10 s 4400 A 104 °F (40 °C) - 30 s 3400 A 104 °F (40 °C) - 1 min 2200 A 104 °F (40 °C) - 3 min 1600 A 104 °F (40 °C) - 10 min | |
| Associated Fuse Rating | 630 A aM at <= 440 V 1000 A BS88 at <= 440 V 1000 A gG at <= 440 V | |
| Average Impedance | 0.12 mOhm - Ith 1000 A 50 Hz | |
| | | |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| [Ui] Rated Insulation Voltage | 1000 V IEC 60158-1 | |
|-------------------------------|---------------------------------|--|
| | 1000 V IEC 60947-4 | |
| | 1000 V BS 775 | |
| | 1500 V VDE 0110 group C | |
| Power Dissipation Per Pole | 48 W AC-3 | |
| | 120 W AC-1 | |
| Standards | EN/IEC 60947-1 | |
| | EN/IEC 60947-4-1 | |
| | JIS C8201-4-1 | |
| | UL 60947-4-1 | |
| | CSA C22.2 No 60947-4-1 | |
| Product Certifications | CB Scheme | |
| | UL | |
| | CSA | |
| | EAC | |
| | CE | |
| | UKCA | |
| Connections - Terminals | bars 2 60 x 5 mm | |
| | Power circuit bolted connection | |
| Tightening Torque | 513.34 lbf.in (58 N.m) | |
| Operating Time | 4080 ms latching | |
| | 50100 ms unlatching | |
| Mechanical Durability | 1 Mcycles | |
| Maximum Operating Rate | 120 cyc/h 104 °F (40 °C) | |
| | | |

Complementary

| Control Circuit Voltage Limits | Latching: 0.851.1 Uc Unlatching: 0.851.1 Uc |
|--------------------------------|--|
| Average Consumption | 620 W DC latching 45 W DC unlatching |

Environment

| Protective Treatment | тс | |
|--|--------------------------------------|--|
| Ambient Air Temperature For Operation | 5158 °F (-1570 °C) | |
| Ambient Air Temperature For Storage | -76176 °F (-6080 °C) | |
| Operating Altitude | 9842.52 ft (3000 m) without derating | |
| Height | 11.97 in (304 mm) | |
| Width | 12.17 in (309 mm) | |
| Depth | 10.04 in (255 mm) | |
| Net Weight | 41.01 lb(US) (18.6 kg) | |

Ordering and shipping details

| Category | US10I1222331 | |
|-------------------|---------------|--|
| Discount Schedule | 0112 | |
| Gtin | 3389110548891 | |
| Returnability | No | |
| Country Of Origin | US | |

Packing Units

Unit Type Of Package 1

PCE

| Number Of Units In Package 1 | 1 | |
|------------------------------|-------------------------|--|
| Package 1 Height | 10.83 in (27.5 cm) | |
| Package 1 Width | 13.39 in (34.0 cm) | |
| Package 1 Length | 13.78 in (35.0 cm) | |
| Package 1 Weight | 36.09 lb(US) (16.37 kg) | |

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information

Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|--|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |