## **Product data sheet**

Specifications





# TeSys F magnetic latching contactor - 3P(3 NO) - 630 A - 380 V AC coil

CR1F630Q7

! Discontinued on: Jul 12, 2021

(!) Discontinued

#### Main

Range	TeSys
Product Name	TeSys F
Product Or Component Type	Magnetic latching contactor
Device Short Name	CR1F
Device Application	Control
Contactor Application	Resistive load Motor control
Utilisation Category	AC-4 AC-3 AC-1
Poles Description	3P
Power Pole Contact Composition	3 NO
[Ue] Rated Operational Voltage	1000 V AC 25200 Hz
[le] Rated Operational Current	630 A (at <104 °F (40 °C)) at <= 440 V AC AC-3 1000 A (at <104 °F (40 °C)) at <= 440 V AC AC-1 560 A (at <104 °F (40 °C)) at <= 440 V AC AC-4
Motor Power Kw	335 kW at 400 V AC 50/60 Hz (AC-4)
Control Circuit Type	AC 50/60 Hz
[Uc] Control Circuit Voltage	380 V AC 50/60 Hz
Irms Rated Making Capacity	6740 A
Rated Breaking Capacity	6300 A at 220440 V 5400 A at 500 V 3200 A at 1000 V 4600 A at 660/690 V
[Icw] Rated Short-Time Withstand Current	5.05 kA 104 °F (40 °C) - 1 s 5.05 kA 104 °F (40 °C) - 5 s 5.05 kA 104 °F (40 °C) - 10 s 4400 A 104 °F (40 °C) - 30 s 3400 A 104 °F (40 °C) - 1 min 2200 A 104 °F (40 °C) - 3 min 1600 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	630 A aM at <= 440 V 1000 A BS88 at <= 440 V 1000 A gG at <= 440 V
Average Impedance	0.12 mOhm - Ith 1000 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60158-1 1000 V IEC 60947-4 1000 V BS 775 1500 V VDE 0110 group C

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Apr 26, 2024 Life Is On Schneider

Power Dissipation Per Pole	48 W AC-3 120 W AC-1
Connections - Terminals	bars 2 60 x 5 mm Power circuit bolted connection
Tightening Torque	513.34 lbf.in (58 N.m)
Operating Time	4080 ms latching 50100 ms unlatching
Mechanical Durability	1 Mcycles
Maximum Operating Rate	120 cyc/h 104 °F (40 °C)

### Complementary

Control Circuit Voltage Limits	Latching: 0.851.1 Uc Unlatching: 0.851.1 Uc
Average Consumption	8 VA AC 50/60 Hz unlatching 2100 VA AC 50/60 Hz latching

#### **Environment**

Protective Treatment	TC
Ambient Air Temperature For Operation	5158 °F (-1570 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Operating Altitude	9842.52 ft (3000 m) without derating
Height	11.97 in (304 mm)
Width	12.17 in (309 mm)
Depth	10.04 in (255 mm)
Net Weight	41.01 lb(US) (18.6 kg)

## Ordering and shipping details

Category	22331-CTR,F-LINE,DC,OPEN,NONREV	
Discount Schedule	112	
Gtin	3389110548921	
Returnability	No	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.83 in (27.5 cm)
Package 1 Width	13.39 in (34 cm)
Package 1 Length	13.78 in (35 cm)
Package 1 Weight	36.09 lb(US) (16.37 kg)

## **Contractual warranty**

Warranty 18 months	
--------------------	--



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov