Product data sheet

Specifications

SQUARE D

Safety switch, general duty, fusible, 200A, 3 pole, 60hp, 240VAC, NEMA 3R, 4 wire, 1 neutral, bolt on hub provision

D324NRB

Product availability: Stock - Normally stocked in distribution facility

Price*: 1,461.00 USD

Main

Product	Single Throw Safety Switch
Duty Rating	General duty
Device Application	Residential
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral (factory installed)
Phase	3 phase
Number Of Poles	3
Current Rating	200 A
Voltage Rating	240 V AC
Enclosure Rating Nema	NEMA 3R
Motor Power Hp	15 hp at 240 V AC 60 Hz for 1 phase motors 25 hp at 240 V AC 60 Hz for 3 phase motors 60 hp at 240 V AC 60 Hz for 3 phase motors

Complementary

Short Circuit Current Rating100 kA maximum depending on fuse H, K or RFuse TypeH, K or RMounting TypeSurfaceElectrical ConnectionLugsWiring Configuration4-wire (3PH + G)Wire SizeAWG 6250 kcmil aluminium/copperTightening Torque275 lbf.in (31.07 N.m) (AWG 6250 kcmil)Depth8.5 in (215.90 mm)Width19 in (482.60 mm)Height29.25 in (742.95 mm)Net Weight56.50 lb(US) (25.63 kg)		
Mounting Type Surface Electrical Connection Lugs Wiring Configuration 4-wire (3PH + G) Wire Size AWG 6250 kcmil aluminium/copper Tightening Torque 275 lbf.in (31.07 N.m) (AWG 6250 kcmil) Depth 8.5 in (215.90 mm) Width 19 in (482.60 mm) Height 29.25 in (742.95 mm)	Short Circuit Current Rating	100 kA maximum depending on fuse H, K or R
Electrical ConnectionLugsWiring Configuration4-wire (3PH + G)Wire SizeAWG 6250 kcmil aluminium/copperTightening Torque275 lbf.in (31.07 N.m) (AWG 6250 kcmil)Depth8.5 in (215.90 mm)Width19 in (482.60 mm)Height29.25 in (742.95 mm)	Fuse Type	H, K or R
Wiring Configuration4-wire (3PH + G)Wire SizeAWG 6250 kcmil aluminium/copperTightening Torque275 lbf.in (31.07 N.m) (AWG 6250 kcmil)Depth8.5 in (215.90 mm)Width19 in (482.60 mm)Height29.25 in (742.95 mm)	Mounting Type	Surface
Wire Size AWG 6250 kcmil aluminium/copper Tightening Torque 275 lbf.in (31.07 N.m) (AWG 6250 kcmil) Depth 8.5 in (215.90 mm) Width 19 in (482.60 mm) Height 29.25 in (742.95 mm)	Electrical Connection	Lugs
Tightening Torque 275 lbf.in (31.07 N.m) (AWG 6250 kcmil) Depth 8.5 in (215.90 mm) Width 19 in (482.60 mm) Height 29.25 in (742.95 mm)	Wiring Configuration	4-wire (3PH + G)
Depth 8.5 in (215.90 mm) Width 19 in (482.60 mm) Height 29.25 in (742.95 mm)	Wire Size	AWG 6250 kcmil aluminium/copper
Width 19 in (482.60 mm) Height 29.25 in (742.95 mm)	Tightening Torque	275 lbf.in (31.07 N.m) (AWG 6250 kcmil)
Height 29.25 in (742.95 mm)	Depth	8.5 in (215.90 mm)
	Width	19 in (482.60 mm)
Net Weight 56.50 lb(US) (25.63 kg)	Height	29.25 in (742.95 mm)
	Net Weight	56.50 lb(US) (25.63 kg)

Environment

Certifications

UL listed file E2875

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	US1DE1A00106
Discount Schedule	DE1A
Gtin	785901461524
Returnability	Yes
Country Of Origin	CA

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.40 in (21.336 cm)
Package 1 Width	19.30 in (49.022 cm)
Package 1 Length	30.80 in (78.232 cm)
Package 1 Weight	44.65 lb(US) (20.253 kg)
Unit Type Of Package 2	PAL
Number Of Units In Package 2	15
Package 2 Height	45.00 in (114.3 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	703.00 lb(US) (318.875 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

REACh Declaration
Compliant
EU RoHS Declaration
China RoHS declaration
Pro-active China RoHS declaration (out of China RoHS legal scope)
Product Environmental Profile
No need of specific recycling operations
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov