Product data sheet

Specification





Fuse carrier, TeSys DF, 3P, 50A, 690VAC, fuse size 14x51mm

DF143C

Product availability: Stock - Normally stocked in distribution facility

Price*: 83.00 USD

Main

Range	TeSys	
Product Name	TeSys DF	
Product Or Component Type	Fuse carrier	
Device Short Name	DF14	
Product Compatibility	DF3EA fuse cartridge striker DF3EN fuse cartridge striker DF14AM auxiliary contact block	
Poles Description	3P	
Fuse Size	14 x 51 mm	
Fuse Type	, aM , gG	
Control Type	Toggle	
[Ue] Rated Operational Voltage	690 V AC 690 V DC	
[le] Rated Operational Current	50 A	
[Ui] Rated Insulation Voltage	690 V AC	
[Uimp] Rated Impulse Withstand Voltage	d 8 kV	
[lpk] Rated Peak Withstand Current	15 kA with tubular links IEC 60269-1	
Short-Circuit Withstand	120 kA 400 V IEC 60947-3 120 kA 500 V IEC 60947-3 80 kA 690 V IEC 60947-3	

Complementary

Standards	EN/IEC 60947-3 EN/IEC 60269-2 UL 4248-1 CSA C22.2 No 4248-1	
Product Certifications	IEC UL Recognized CSA EAC	
Mounting Support	35 mm symmetrical DIN rail	
Mounting Position	Vertical +/- 23°)	
Connections - Terminals	nections - Terminals screw clamp terminals 1 0.000.04 in² (2.525 mm²)rigid screw clamp terminals 2 0.000.02 in² (2.510 mm²)rigid screw clamp terminals 1 0.000.04 in² (2.525 mm²)flexible with or without screw clamp terminals 2 0.000.02 in² (2.510 mm²)flexible with or without	
Tightening Torque	30.98 lbf.in (3.5 N.m)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	4.36 in (110.8 mm)	
Width	3.11 in (79 mm)	
Depth	3.01 in (76.5 mm)	
Net Weight	0.93 lb(US) (0.420 kg)	
Quantity Per Set	Set of 2	

Environment

Ambient Air Temperature For Storage	-40176 °F (-4080 °C)	
Ambient Air Temperature For -4140 °F (-2060 °C) with derating above 20°C Departion		
Ip Degree Of Protection	IP20 conforming to IEC 60529	
Protective Treatment	ТН	
Fire Resistance	1760 °F (960 °C) IEC 60695-2-1	
Compatibility Code	DF14	

Ordering and shipping details

Category	US10CP121714	
Discount Schedule	0CP1	
Gtin	3389119407410	
Returnability	Yes	
Country Of Origin	US	

Packing Units

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	4.37 in (11.100 cm)	
Package 1 Width	3.13 in (7.950 cm)	
Package 1 Length	3.03 in (7.700 cm)	
Package 1 Weight	11.82 oz (335.000 g)	
Unit Type Of Package 2	BB1	
Number Of Units In Package 2	2	
Package 2 Height	3.35 in (8.500 cm)	
Package 2 Width	4.80 in (12.200 cm)	
Package 2 Length	7.17 in (18.200 cm)	
Package 2 Weight	27.20 oz (771.000 g)	
Unit Type Of Package 3	S03	
Number Of Units In Package 3	24	
Package 3 Height	11.81 in (30.000 cm)	
Package 3 Width	11.81 in (30.000 cm)	
Package 3 Length	15.75 in (40.000 cm)	
Package 3 Weight	21.38 lb(US) (9.697 kg)	

Contractual warranty

Warranty

18 months

Sustainability Screen Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
②	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations Circularity Profile
California Proposition 65	WARNING: Cancer - www.P65Warnings.ca.gov