# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

SQUARE D



# Square D - PowerLogic Energy Meter, Basic 200A, 0.75"X1.10" ID, 2CT's

EMB2021

! Discontinued on: Dec 31, 2022



Product availability: Non-Stock - Not normally stocked in distribution facility

### Main

Range	PowerLogic
Product Name	PowerLogic ENERGY METER
Product Or Component Type	Energy meter
Device Application	Energy monitoring

# Complementary

Type Of Measurement	Energy consumption
	Power
	Peak demand power
	Reactive power
	Power factor
	Voltage
	Current
Measurement Accuracy	+/- 1 %
Measurement Voltage	120 V AC between phase and neutral
measurement voltage	240 V AC between phases
	210 V No bothoon phagos
[Us] Rated Supply Voltage	120 V AC - 2510 %
Network Frequency	60 Hz
	50 Hz
Line Rated Current	200 A
Display Type	Backlit LCD
Display Size	1.2 x 3.8 inch
Information Displayed	Energy consumption
	Power
	Power maximum)
	Reactive power
	Power factor
	Voltage
	Current
Sampling Rate	1280 Hz
Provided Equipment	2 x current transformer
Ct Size	0.75 x 1.10 inch
Standards	ANSI C12.1
Product Certifications	UL UL 3111-1 CUL
Width	7.60 in (193 mm)
Depth	Meter 2.99 in (76 mm)

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Height 8.31 in (211 mm)

### **Environment**

Isolation Voltage	2500 V
Relative Humidity	095 % non-condensing
Ambient Air Temperature For Operation	32122 °F (050 °C)
Ambient Air Temperature For Storage	-40158 °F (-4070 °C)

# Ordering and shipping details

Category	US10PL109779
Discount Schedule	0PL1
Gtin	785901539322
Returnability	Yes
Country Of Origin	US

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.88 in (20.003 cm)
Package 1 Width	8.75 in (22.225 cm)
Package 1 Length	12.00 in (30.48 cm)
Package 1 Weight	4.90 lb(US) (2.223 kg)

# **Contractual warranty**

Warranty 18 months

### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

## Well-being performance

$\checkmark$	Mercury Free
<b>⊘</b>	Rohs Exemption Information

Reach Regulation	REACh Declaration	
Eu Rohs Directive	Compliant with Exemptions	
China Rohs Regulation	China RoHS declaration	

Yes

Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov