



# Circuit breaker, FA, 240V, 60A, 3 pole, SPECIAL

FAL320608022

#### Main

Product Or Component Type	Circuit breaker
Trip Unit Technology	Thermal-magnetic

#### Complementary

Line Rated Current	60 A	
Number Of Poles	3P	
Breaking Capacity Code	A	
Mounting Mode	Unit mount	
Magnetic Hold Current	800 A	
Magnetic Tripping Current	1450 A	
Electrical Connection	Lugs, load Lugs, line	
Terminal Identifier	AL100FA	
Phase Connection	ABC	
Height	6.4 in (162.56 mm)	
Width	4.5 in (114.30 mm)	
Depth	4.13 in (104.90 mm)	
Circuit Breaker Application	HACR rated	

#### **Environment**

Certifications	UL Listed
	CSA

## Ordering and shipping details

Category	00901-FAL 240V BREAKERS & SWITCH	
Discount Schedule	DE2	
Gtin	00785901776864	
Returnability	No	
Country Of Origin	MX	

## **Packing Units**

Unit Type Of Package 1	PCE		

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Number Of Units In Package 1

1

## **Contractual warranty**

Warranty

18 months

## **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive	Not applicable, out of EU RoHS legal scope
California Proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.For more information go to www.p65warnings.ca.gov