

# Product data sheet

Specifications



## TeSys Deca - auxiliary contact mounted on left hand side

GK2AX12

Discontinued on: Jul 12, 2021

Discontinued

### Main

Range	TeSys
Device Short Name	GK2AX
Product Or Component Type	Fault signalling contact
Product Compatibility	GK3EF
Range Compatibility	TeSys GK3 GK3EF circuit breaker
Mounting Location	Left side
Auxiliary Contacts Operation	Fault signal 1 NO
Pole Contact Composition	1 NO
Quantity Per Set	Set of 10

### Complementary

[Ui] Rated Insulation Voltage	500 V IEC 60947-1
[Ue] Rated Operational Voltage	500 V
[Ith] Conventional Free Air Thermal Current	6 A
Protection Type	GB2CB... circuit breaker GG fuse 6 A
Rated Operational Power In Va	360 VA 48 V AC-15 20000 cycles 6 A 500 VA 110...127 V AC-15 20000 cycles 4.5 A 800 VA 220...240 V AC-15 20000 cycles 3.5 A 850 VA 380...415 V AC-15 20000 cycles 2.2 A 700 VA 440 V AC-15 20000 cycles 1.5 A 700 VA 500 V AC-15 20000 cycles 1.5 A
Rated Operational Power In W	180 W 24 V DC-13 1000 cycles 240 W 48 V DC-13 1000 cycles 180 W 60 V DC-13 1000 cycles 140 W 110 V DC-13 1000 cycles 120 W 220 V DC-13 1000 cycles
Height	3.15 in (80 mm)
Width	0.35 in (8.8 mm)
Depth	4.13 in (105 mm)
Net Weight	0.06 lb(US) (0.025 kg)

### Environment

Environmental Characteristic	Normal environment
------------------------------	--------------------

### Ordering and shipping details

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Category	22641-PAN,DISCONNECT,IEC ***OBSOLETE***
Discount Schedule	I
Gtin	3389110257021
Returnability	No
Country Of Origin	FR

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.55 in (1.4 cm)
Package 1 Width	2.76 in (7 cm)
Package 1 Length	3.15 in (8 cm)
Package 1 Weight	1.20 oz (34 g)

## Contractual warranty

Warranty	18 months
----------	-----------

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

- [Learn more about Green Premium >](#)
- [Guide to assess a product’s sustainability >](#)



RoHS/REACH

Well-being performance

<div>✓</div> Mercury Free	
<div>✓</div> Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Compliant <a href="#">EU RoHS Declaration</a>
China Rohs Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="#">www.P65Warnings.ca.gov</a>