## **Product data sheet**

Specification





# Switch disconnector fuse, TeSys GS, 3P + N, 4NO, 32A, fuse type NFC, size 10x38mm

GS1DD4

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 724.00 USD

#### Main

Range	TeSys	
Product Name	TeSys GS	
Device Short Name	GS1 DD	
Product Or Component Type	Switch-disconnector-fuse	
Device Application	Protection	
Poles Description	3P + Nc	
Protected Poles Description	3t	
Contacts Type And Composition	4 NO	
[Ith] Conventional Free Air Thermal Current	32 A (at 104 °F (40 °C))	
[le] Rated Operational Current	20 A 440 V 2 poles in series per phase DC-23A 20 A 440 V 2 poles in series per phase DC-23B 32 A 400 V AC-23A 32 A 400 V AC-23B 32 A 500 V AC-23B 32 A 500 V AC-23B 32 A 690 V AC-23B 32 A 690 V AC-23A 32 A 690 V AC-23A	
Fuse Type	NFC	
Fuse Size	10 x 38 mm	
Network Type	DC AC	
Network Frequency	50/60 Hz	

#### Complementary

Type Of Operating Handle	External frontal External left side Direct frontal External right side
Mounting Support	Plate Rail
[Ui] Rated Insulation Voltage	800 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
Rated Operational Power In W	15 kW 400 V 18.5 kW 500 V 25 kW 690 V
Making Capacity	320 A 400 V AC-23B

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Breaking Capacity	256 A 400 V AC-23B)	
Short-Circuit Withstand	5.5 kA	
Mechanical Durability	20000 cycles	
Electrical Durability	1500 cycles AC-23A 1500 cycles AC-23B 300 cycles DC-23A 300 cycles DC-23B	
Connections - Terminals	Power circuit screw-clamp terminals 0.000.02 in² (2.516 mm²) flexible	
[Icm] Rated Short-Circuit Making Capacity	g 100 kA 400 V with protection by gG fuses	
Tightening Torque	Power circuit 26.55 lbf.in (3 N.m) screw-clamp terminals	

#### **Environment**

Standards	IEC 60947-3	
Product Certifications	CE	
Protective Treatment	тн	
Ip Degree Of Protection	IP20 IEC 60529 with terminal cover)	
Ambient Air Temperature For Operation	-4158 °F (-2070 °C)	
Ambient Air Temperature For Storage	-40176 °F (-4080 °C)	
Fire Resistance	1760 °F (960 °C) body IEC 60695-2-1	
Height	3.86 in (98 mm)	
Width	3.78 in (96 mm)	
Depth	4.41 in (112 mm)	
Net Weight	1.10 lb(US) (0.5 kg)	

## Ordering and shipping details

Category	US1CP1018402	
Discount Schedule	CP10	
Gtin	3389110120110	
Returnability	No	
Country Of Origin	FR	

## **Packing Units**

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	3.54 in (9.000 cm)	
Package 1 Width	4.13 in (10.500 cm)	
Package 1 Length	4.53 in (11.500 cm)	
Package 1 Weight	17.28 oz (490.000 g)	
Unit Type Of Package 2	S03	
Number Of Units In Package 2	18	
Package 2 Height	11.81 in (30.000 cm)	
Package 2 Width	11.81 in (30.000 cm)	

Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	20.57 lb(US) (9.330 kg)

### **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium\*

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

REACh Declaration
Compliant
EU RoHS Declaration
China RoHS declaration
Product out of China RoHS scope. Substance declaration for your information.
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
End of Life Information
WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov