# Product data sheet

Specifications





Advanced touchscreen panel, Harmony GTO, 5.7 Color Touch QVGA TFT, coated display without logo

HMIGTO2300FCW

① Discontinued

(!) Discontinued on: Jun 15, 2023

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Range Of Product	Harmony GTO
Product Or Component Type	Advanced touchscreen panel
Display Colour	65536 colours
Display Size	5.7 inch
Supply	External source
Battery Type	Lithium internal RAM 100 days 5 day(s) 10 year(s)

#### Complementary

Terminal Type	Touchscreen display
Display Type	Backlit colour TFT LCD
Display Resolution	320 x 240 pixels QVGA
Touch Sensitive Zone	1024 x 1024
Touch Panel	Resistive film, 1000000 cycles
Backlight Lifespan	50000 hours white 77 °F (25 °C)
Brightness	16 levels by touch panel 16 levels by software
Character Font	Korean ASCII (European characters) Chinese (simplified Chinese) Taiwanese (traditional Chinese) Japanese (ANK, Kanji)
[Us] Rated Supply Voltage	24 V DC
Supply Voltage Limits	19.228.8 V
Inrush Current	30 A
Maximum Power Consumption In W	6.5 W when power is not supplied to external devices 4.5 W when backlight is OFF 5 W when backlight is dimmed

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

10.5 W

Software Designation  Memory Description	Status LED green, steady offline Status LED green, steady operating Status LED orange, flashing software starting up Status LED red, steady power supply (ON) Status LED clear, faded power supply (OFF) COM2 LED yellow, steady data is being transmitted COM2 LED yellow, faded no data transmission SD card LED green, steady card is inserted SD card LED green, faded card is not inserted or is not being accessed  Vijeo Designer configuration software >= V6.1
Data Backed Up	128 kB internal RAM SRAM)
Downloadable Protocols	Schneider Electric Modicon Modbus Schneider Electric Modicon Uni-TE Schneider Electric Modicon Modbus Plus Schneider Electric Modicon FIPWAY Mitsubishi Melsec third party protocols Omron Sysmac third party protocols Rockwell Automation Allen-Bradley third party protocols Siemens Simatic third party protocols
Integrated Connection Type	COM1 serial link SUB-D 9 RS232C 2400115200 bps COM2 serial link RJ45 RS485 2400115200 bps COM2 serial link RJ45 RS485 187.5 kbps Siemens MPI USB 2.0 type A USB 2.0 type mini B
Product Mounting	Flush mounting
Fixing Mode	by 4 screw clamps
Front Material	PPT
Enclosure Material	PPT
Type Of Cooling	Natural convection
Width	6.67 in (169.5 mm)
Height	5.39 in (137 mm)
Depth	2.34 in (59.5 mm)
Net Weight  Environment	1.76 lb(US) (0.8 kg)
Standards	UL 508 EN 61131-2 IEC 61000-6-2
Product Certifications	cULus KCC C-tick CE UKCA UKEX
Ambient Air Temperature For Operation	32122 °F (050 °C)
Ambient Air Temperature For Storage	-4140 °F (-2060 °C)
Relative Humidity	1090 % without condensation
Operating Altitude	< 6561.68 ft (2000 m)
Ip Degree Of Protection	IP20 IEC 60529 rear panel) IP65 IEC 60529 front panel)
Nema Degree Of Protection	NEMA 4X front panel (indoor use)

147 m/s $^2$  3 chocks in each direction X, Y and Z EN/IEC 61131-2

Shock Resistance

Vibration Resistance	3.5 mm 59 Hz) - X, Y, Z directions for 10 cycles (approx. 100 min) - EN/IEC 61131-2 1 gn 9150 Hz) - X, Y, Z directions for 10 cycles (approx. 100 min) - EN/IEC 61131-2
Resistance To Electrostatic	6 kV contact discharge IEC 61000-4-2 level 3

# Ordering and shipping details

	· · · · ·
Category	US10MC222569
Discount Schedule	0MC2
Gtin	3606480841927
Returnability	No
Country Of Origin	CN

### **Packing Units**

_	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.91 in (15.0 cm)
Package 1 Width	7.28 in (18.5 cm)
Package 1 Length	9.45 in (24.0 cm)
Package 1 Weight	2.49 lb(US) (1.129 kg)
Unit Type Of Package 2	S03
Number Of Units In Package 2	4
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	9.99 lb(US) (4.532 kg)

### Sustainability Screen Premium

Green Premium<sup>TM</sup> label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Rohs Exemption Information

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov