





Circuit breaker, PowerPacT J, 250A, 3 pole, 480VAC, 65kA, lugs, Micrologic 6.2A, 80%, mission critical

JJL34250WU44X

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 9,206.00 USD

Main

Range	PowerPact
Product Name	PowerPact J
Product Or Component Type	Circuit breaker
Device Application	Distribution

Complementary

Line Rated Current	250 A
Number Of Poles	3P
Control Type	Toggle
Breaking Capacity Code	J
Breaking Capacity	100 kA 240 V AC 50/60 Hz UL 489 65 kA 480 V AC 50/60 Hz UL 489 25 kA 600 V AC 50/60 Hz UL 489 20 kA 250 V DC UL 489
[Ue] Rated Operational Voltage	480/277 V AC 50/60 Hz IEC 60947-3
Network Frequency	50/60 Hz
[Ics] Rated Service Breaking Capacity	65 kA 220/240 V AC 50/60 Hz IEC 60947-2 35 kA 380/440/415 V AC 50/60 Hz IEC 60947-2 18 kA 500/525 V AC 50/60 Hz IEC 60947-2 20 kA 250 V DC IEC 60947-2 20 kA 500 V DC IEC 60947-2
[Uimp] Rated Impulse Withstand Voltage	8 kV IEC 60947-2
Trip Unit Technology	Electronic, ammeter, MicroLogic 6.2 A, LSIG
Continuous Current Rating	80 %
[Ui] Rated Insulation Voltage	750 V IEC 60947-2
Trip Unit Name	MicroLogic 6.2 A
Protection Type	Overload protection Short-circuit protection
Suitability For Isolation	Yes IEC 60947-2
Utilisation Category	Category A
Awg Gauge	AWG 3/0350 kcmil aluminium/copper terminals

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ready 1 LED green Alarm 1 LED 10% ir orange Alarm 2		
Lug	Local Signalling	Alarm 1 LED 90 % Ir orange) Alarm 1 LED 105 % Ir red)
Electrical Connection Lugs, line Lugs, load Terminal Identifier AL250JD Long Time Pick-Up Adjustment Range Mounting Height 4.5 in (114.30 mm) Tightening Torque 221.27 lbf.in (25 N.m) 0.150.29 in² (95185 mm²) (AWG 3/0350 kcmil) Number Of Slots 2 auxiliary switch OF plug-in) 1 alarm switch SD plug-in) 1 overcurrent trip switch SDE plug-in) 1 voltage release MN or MX plug-in) Power Wire Stripping Length 0.98 in (25 mm) Height 7.52 in (191 mm) Width 4.09 in (104 mm) Depth 3.39 in (86 mm) Net Weight 5.29 lb(US) (2.4 kg) Phase Connection AB Communication Interface Modbus Ethernet	Mounting Mode	Unit mount lug)
Lugs, load Terminal Identifier AL250JD Long Time Pick-Up Adjustment Range 0.251 x ln Range Mounting Height 4.5 in (114.30 mm) Tightening Torque 221.27 lbf.in (25 N.m) 0.150.29 in² (95185 mm²) (AWG 3/0350 kcmil) Number Of Slots 2 auxiliary switch OF plug-in) 1 alarm switch SD plug-in) 1 overcurrent trip switch SDE plug-in) 1 voltage release MN or MX plug-in) Power Wire Stripping Length 0.98 in (25 mm) Height 7.52 in (191 mm) Width 4.09 in (104 mm) Depth 3.39 in (86 mm) Net Weight 5.29 lb(US) (2.4 kg) Phase Connection AB Communication Interface Modbus Ethernet	Mounting Support	Lug
Long Time Pick-Up Adjustment Range Mounting Height 4.5 in (114.30 mm) Tightening Torque 221.27 lbf.in (25 N.m) 0.150.29 in² (95185 mm²) (AWG 3/0350 kcmil) Number Of Slots 2 auxiliary switch OF plug-in) 1 alarm switch SDD plug-in) 1 overcurrent trip switch SDE plug-in) 1 voltage release MN or MX plug-in) Power Wire Stripping Length 7.52 in (191 mm) Width 4.09 in (104 mm) Depth 3.39 in (86 mm) Net Weight 5.29 lb(US) (2.4 kg) Phase Connection AB Communication Interface Modbus Ethernet	= 255,o	
Range Mounting Height 4.5 in (114.30 mm) Tightening Torque 221.27 lbf.in (25 N.m) 0.150.29 in² (95185 mm²) (AWG 3/0350 kcmill) Number Of Slots 2 auxiliary switch OF plug-in)	Terminal Identifier	AL250JD
Tightening Torque 221.27 lbf.in (25 N.m) 0.150.29 in² (95185 mm²) (AWG 3/0350 kcmil) Number Of Slots 2 auxiliary switch OF plug-in)		0.251 x ln
Number Of Slots 2 auxiliary switch OF plug-in) 1 alarm switch SD plug-in) 1 overcurrent trip switch SDE plug-in) 1 voltage release MN or MX plug-in) Power Wire Stripping Length 0.98 in (25 mm) Height 7.52 in (191 mm) Width 4.09 in (104 mm) Depth 3.39 in (86 mm) Net Weight 5.29 lb(US) (2.4 kg) Phase Connection AB Communication Interface Modbus Ethernet	Mounting Height	4.5 in (114.30 mm)
1 alarm switch SD plug-in) 1 overcurrent trip switch SDE plug-in) 1 voltage release MN or MX plug-in) Power Wire Stripping Length 0.98 in (25 mm) Height 7.52 in (191 mm) Width 4.09 in (104 mm) Depth 3.39 in (86 mm) Net Weight 5.29 lb(US) (2.4 kg) Phase Connection AB Communication Interface Modbus Ethernet	Tightening Torque	221.27 lbf.in (25 N.m) 0.150.29 in² (95185 mm²) (AWG 3/0350 kcmil)
Height 7.52 in (191 mm) Width 4.09 in (104 mm) Depth 3.39 in (86 mm) Net Weight 5.29 lb(US) (2.4 kg) Phase Connection AB Communication Interface Modbus Ethernet	Number Of Slots	1 alarm switch SD plug-in) 1 overcurrent trip switch SDE plug-in)
Width 4.09 in (104 mm) Depth 3.39 in (86 mm) Net Weight 5.29 lb(US) (2.4 kg) Phase Connection AB Communication Interface Modbus Ethernet	Power Wire Stripping Length	0.98 in (25 mm)
Depth 3.39 in (86 mm) Net Weight 5.29 lb(US) (2.4 kg) Phase Connection AB Communication Interface Modbus Ethernet	Height	7.52 in (191 mm)
Net Weight 5.29 lb(US) (2.4 kg) Phase Connection AB Communication Interface Modbus Ethernet	Width	4.09 in (104 mm)
Phase Connection AB Communication Interface Modbus Ethernet	Depth	3.39 in (86 mm)
Communication Interface Modbus Ethernet	Net Weight	5.29 lb(US) (2.4 kg)
Ethernet	Phase Connection	AB
Circuit Breaker Application HACR rated	Communication Interface	
	Circuit Breaker Application	HACR rated

Environment

Quality Labels	CE
Standards	UL CSA NEMA NOM-003-SCFI-2000 IEC 60947-2
Product Certifications	UL CSA NOM
Ip Degree Of Protection	Front cover IP40
Pollution Degree	3 IEC 60947-1
Ambient Air Temperature For Operation	-13158 °F (-2570 °C)
Ambient Air Temperature For Storage	-58185 °F (-5085 °C)
Operating Altitude	< 6561.68 ft (2000 m) without derating 5000 m with derating

Ordering and shipping details

Category	US10DE201107
Discount Schedule	0DE2
Gtin	3606486996430
Returnability	Yes

Country Of Origin US

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.13 in (13.018 cm)
Package 1 Width	7.25 in (18.415 cm)
Package 1 Length	8.44 in (21.433 cm)
Package 1 Weight	6.00 lb(US) (2.722 kg)

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Mercury Free	
②	Rohs Exemption Information	Yes
	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov