# Product data sheet

Specifications



SQUARE D



Circuit breaker

## Circuit breaker, PowerPacT J, 150A, 3 pole, 600VAC, 50kA, I-Line, thermal magnetic, 80%, CBA

JLA361506

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Price\*: 7,299.00 USD

#### Main

Product Or Component Type

Complementary		
Line Rated Current	150 A	
Number Of Poles	3P	
Control Type	Toggle	
Breaking Capacity Code	L	
Breaking Capacity	125 kA 240 V AC 50/60 Hz UL 489 100 kA 480 V AC 50/60 Hz UL 489 50 kA 600 V AC 50/60 Hz UL 489 20 kA 250 V DC UL 489 50 kA 500 V DC UL 489	
[Ue] Rated Operational Voltage	600 V AC 50/60 Hz IEC 60947-3	
Network Frequency	50/60 Hz	
[Ics] Rated Service Breaking Capacity	125 kA 220/240 V AC 50/60 Hz IEC 60947-2 100 kA 380/440/415 V AC 50/60 Hz IEC 60947-2 50 kA 500/525 V AC 50/60 Hz IEC 60947-2 20 kA 250 V DC IEC 60947-2 20 kA 500 V DC IEC 60947-2	
[Uimp] Rated Impulse Withstand Voltage	8 kV IEC 60947-2	
Trip Unit Technology	Thermal-magnetic	
Magnetic Tripping Current	1750 A	
Magnetic Hold Current	750 A	
Continuous Current Rating	80 %	
[Ui] Rated Insulation Voltage	750 V IEC 60947-2	
Protection Type	Overload protection Short-circuit protection	
Suitability For Isolation	Yes IEC 60947-2	
Utilisation Category	Category A	
Awg Gauge	AWG 4AWG 4/0 aluminium/copper terminal	
Local Signalling	Switched off (OFF) 1 trip indicator green)	
Mounting Mode	I-Line bracket)	
Mounting Support	Bracket	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Electrical Connection	I-Line connection, line	
	Lugs, load	
	- 0 - 7	
Terminal Identifier	AL175JD	
Long Time Pick-Up Adjustment Range	0.251 x In	
Mounting Height	4.5 in (114.30 mm)	
Tightening Torque	221.27 lbf.in (25 N.m) 0.040.15 in <sup>2</sup> (2595 mm <sup>2</sup> ) (AWG 4AWG 4/0)	
Number Of Slots	2 auxiliary switch OF plug-in)	
	1 alarm switch SD plug-in)	
	1 overcurrent trip switch SDE plug-in)	
	1 voltage release MN or MX plug-in)	
	······································	
Power Wire Stripping Length	0.98 in (25 mm)	
Height	7.52 in (191 mm)	
Width	4.09 in (104 mm)	
Depth	3.39 in (86 mm)	
<u></u>		
Net Weight	5.29 lb(US) (2.4 kg)	
Phase Connection	СВА	
Communication Interface	Modbus	
Circuit Breaker Application	HACR rated	

### Environment

Quality Labels	CE	
Standards	UL CSA NEMA NOM-003-SCFI-2000 IEC 60947-2	
Product Certifications	UL CSA NOM	
Ip Degree Of Protection	Front cover IP40	
Pollution Degree	3	
Ambient Air Temperature For Operation	28158 °F (-270 °C)	
Ambient Air Temperature For Storage	-58185 °F (-5085 °C)	
Operating Altitude	< 6561.68 ft (2000 m) without derating 5000 m with derating	

# Ordering and shipping details

Category	US10DE201122	
Discount Schedule	0DE2	
Returnability	Yes	
Country Of Origin	US	

## **Packing Units**

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	5.38 in (13.653 cm)	

 Package 1 Width
 8.13 in (20.638 cm)

 Package 1 Length
 14.63 in (37.148 cm)

 Package 1 Weight
 4.50 lb(US) (2.041 kg)

### **Contractual warranty**

Warranty

18 months

### Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
 Rohs Exemption Information Yes
 Pvc Free

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov