





## Motor circuit protector, PowerPacT J, 250A, 3 pole, 600VAC, 50kA, lugs, thermal magnetic, 80%

JLM36250M75

Motor Circuit Protector

250 A

Discontinued on: Mar 6, 2023



Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

**Product Or Component Type** 

Complementary

**Line Rated Current** 

**Protection Type** 

**Suitability For Isolation** 

**Utilisation Category** 

Awg Gauge

**Local Signalling** 

**Mounting Mode** 

**Mounting Support** 

**Number Of Poles** 3P **Control Type** Toggle **Breaking Capacity Code Breaking Capacity** 125 kA 240 V AC 50/60 Hz UL 489 100 kA 480 V AC 50/60 Hz UL 489 50 kA 600 V AC 50/60 Hz UL 489 20 kA 250 V DC UL 489 50 kA 500 V DC UL 489 [Ue] Rated Operational Voltage 600 V AC 50/60 Hz IEC 60947-3 **Network Frequency** 50/60 Hz [Ics] Rated Service Breaking 125 kA 220/240 V AC 50/60 Hz IEC 60947-2 Capacity 100 kA 380/440/415 V AC 50/60 Hz IEC 60947-2 50 kA 500/525 V AC 50/60 Hz IEC 60947-2 20 kA 250 V DC IEC 60947-2 20 kA 500 V DC IEC 60947-2 [Uimp] Rated Impulse Withstand Voltage 8 kV IFC 60947-2 **Trip Unit Technology** Thermal-magnetic [Ith] Conventional Free Air 117...217 A Thermal Current **Magnetic Tripping Current** 2500 A **Magnetic Hold Current** 1250 A **Continuous Current Rating** 80 % [Ui] Rated Insulation Voltage 750 V IEC 60947-2

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Overload protection Short-circuit protection

Yes IEC 60947-2

Category A

Unit mount lug)

AWG 3/0...350 kcmil aluminium/copper terminals

Switched off (OFF) 1 trip indicator green)

Electrical Connection	Lugs, line Terminal nut, load	
Terminal Identifier	AL250JD	
Long Time Pick-Up Adjustment Range	0.251 x ln	
Tightening Torque	221.27 lbf.in (25 N.m) 0.150.29 in² (95185 mm²) (AWG 3/0350 kcmil)	
Number Of Slots	2 auxiliary switch OF plug-in) 1 alarm switch SD plug-in) 1 overcurrent trip switch SDE plug-in) 1 voltage release MN or MX plug-in)	
Power Wire Stripping Length	0.98 in (25 mm)	
Height	7.52 in (191 mm)	
Width	4.09 in (104 mm)	
Depth	3.39 in (86 mm)	
Net Weight	5.29 lb(US) (2.4 kg)	
Communication Interface	Modbus	

### **Environment**

Quality Labels	CE	
Standards	UL CSA NEMA NOM-003-SCFI-2000 IEC 60947-2	
Product Certifications	UL CSA NOM	
Ip Degree Of Protection	Front cover IP40	
Pollution Degree	3	
Ambient Air Temperature For Operation	28158 °F (-270 °C)	
Ambient Air Temperature For Storage	-58185 °F (-5085 °C)	
Operating Altitude	< 6561.68 ft (2000 m) without derating 5000 m with derating	

# Ordering and shipping details

Category	US10DE201127
Discount Schedule	0DE2
Gtin	785901954231
Returnability	Yes
Country Of Origin	US

# Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.13 in (13.018 cm)
Package 1 Width	7.25 in (18.415 cm)
Package 1 Length	8.44 in (21.433 cm)

Package 1 Weight

5.00 lb(US) (2.268 kg)

### **Contractual warranty**

Warranty

Apr 25, 2024

18 months

## Sustainability Screen Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

	Mercury Free	
<b>②</b>	Rohs Exemption Information	Yes
<b>⊘</b>	Pvc Free	

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov