Product data sheet

Specifications





Circuit breaker

Circuit breaker, PowerPacT J, 250A, 3 pole, 600VAC, 100kA, I-Line, Micrologic 3.2, 80%, ABC

JRA36250U31X

Product availability: Stock - Normally stocked in distribution facility

Price*: 10,102.00 USD

Main

Product Or Component Type

Complementary Line Rated Current 250 A Number Of Poles 3P Control Type Toggle **Breaking Capacity Code** R **Breaking Capacity** 200 kA 240 V AC 50/60 Hz UL 489 200 kA 480 V AC 50/60 Hz UL 489 100 kA 600 V AC 50/60 Hz UL 489 [Ue] Rated Operational Voltage 600 V AC 50/60 Hz IEC 60947-3 **Network Frequency** 50/60 Hz [Ics] Rated Service Breaking 150 kA 220/240 V AC 50/60 Hz IEC 60947-2 Capacity 125 kA 380/440/415 V AC 50/60 Hz IEC 60947-2 75 kA 500/525 V AC 50/60 Hz IEC 60947-2 20 kA 690 V AC 50/60 Hz IEC 60947-2 [Uimp] Rated Impulse Withstand 8 kV IEC 60947-2 Voltage Trip Unit Technology Electronic, standard, MicroLogic 3.2, LI **Continuous Current Rating** 80 % [Ui] Rated Insulation Voltage 750 V IEC 60947-2 Trip Unit Name MicroLogic 3.2 **Protection Type** Overload protection Short-circuit protection Suitability For Isolation Yes IEC 60947-2 Utilisation Category Category A Awg Gauge AWG 3/0...350 kcmil aluminium/copper terminals Local Signalling Ready 1 LED green) Alarm 1 LED 90 % Ir orange) Alarm 1 LED 105 % Ir red) Switched off (OFF) 1 trip indicator green) Mounting Mode I-Line bracket) **Mounting Support** Bracket **Electrical Connection** I-Line connection, line Lugs, load

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Terminal Identifier	AL250JD
Long Time Pick-Up Adjustment Range	0.251 x ln
Mounting Height	4.5 in (114.30 mm)
Tightening Torque	221.27 lbf.in (25 N.m) 0.150.29 in ² (95185 mm ²) (AWG 3/0350 kcmil)
Number Of Slots	2 auxiliary switch OF plug-in) 1 alarm switch SD plug-in) 1 overcurrent trip switch SDE plug-in) 1 voltage release MN or MX plug-in)
Power Wire Stripping Length	0.98 in (25 mm)
Height	7.52 in (191 mm)
Width	4.09 in (104 mm)
Depth	3.39 in (86 mm)
Net Weight	5.29 lb(US) (2.4 kg)
Phase Connection	ABC
Communication Interface	Modbus
Circuit Breaker Application	HACR rated

Environment

Quality Labels	CE
Standards	UL CSA NEMA NOM-003-SCFI-2000 IEC 60947-2
Product Certifications	UL CSA NOM
Ip Degree Of Protection	Front cover IP40
Pollution Degree	3
Ambient Air Temperature For Operation	-13158 °F (-2570 °C)
Ambient Air Temperature For Storage	-58185 °F (-5085 °C)
Operating Altitude	< 6561.68 ft (2000 m) without derating 5000 m with derating

Ordering and shipping details

Category	US10DE201109
Discount Schedule	0DE2
Gtin	785901951162
Returnability	No
Country Of Origin	US

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.38 in (13.653 cm)
Package 1 Width	8.13 in (20.638 cm)

Package 1 Length

14.63 in (37.148 cm)

Package 1 Weight

7.13 lb(US) (3.235 kg)

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov