Product data sheet

Specifications

Thermal overload relays, TeSys Deca, remote electrical tripping, 380...400V AC

LA7D03Q

⊘ Discontinued

Main

Range	TeSys
Product Or Component Type	Electrical remote tripping
Device Short Name	LA7D
Accessory / Separate Part Category	Electrical accessory
Product Compatibility	LR3D15.. LR3D35.. LR3D43.. LRD43.. LRD15.. LR2D LRD33.. LR3D33..
[Uc] Control Circuit Voltage	380/400 V AC 50/60 Hz

Complementary

Maximum Inrush Power In Va	100 VA
Net Weight	0.20 lb(US) (0.09 kg)

Ordering and shipping details

Category	22341-CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
Gtin	3389110055153
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.97 in (5.0 cm)
Package 1 Width	1.89 in (4.8 cm)
Package 1 Length	1.89 in (4.8 cm)
Package 1 Weight	3.70 oz (105.0 g)

Contractual warranty

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| **Warranty** | 18 months |

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information   Yes

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.