Product data sheet

Specifications





Auxiliary contact block, TeSys Deca, 1NO + 1NC, front mounting, screw clamp terminals, EN 50012

LADN11P

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 24.84 USD

Μ	ai	n

Range	TeSys
	TeSys Deca
Product Name	TeSys Deca
Product Or Component Type	Auxiliary contact block
Device Short Name	LADN
Range Compatibility	TeSys D LC1D80004D115004
	TeSys F LC1F
	TeSys F CR1F
	TeSys Deca LC1D80004D115004
Mounting Location	Front
Pole Contact Composition	1 NO + 1 NC
Contacts Operation	Instantaneous
[Ue] Rated Operational Voltage	690 V AC 25400 Hz
[le] Rated Operational Current	6 A at 120 V AC-15
	1.04 A at 690 V AC-15
	0.55 A at 125 V DC-13
	0.1 A at 600 V DC-13
[Ui] Rated Insulation Voltage	690 V IEC 60947-5-1
	600 V UL 60947-5-1
	600 V CSA C22.2 No 60947-5-1
[Ith] Conventional Free Air Thermal Current	10 A (at 140 °F (60 °C))
Standards	EN/IEC 60947-5-1
	GB/T 14048.5
	EN 50012
	EN/IEC 60947-5-1
Product Certifications	IECEE CB Scheme
	UL
	CSA
	CCC
	EAC
	UKCA

Complementary

Irms Rated Making Capacity	140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1
Permissible Short-Time Rating	100 A 140 °F (60 °C) 1 s 120 A 140 °F (60 °C) 500 ms 140 A 140 °F (60 °C) 100 ms
Protection Type	GG fuse 10 A

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Mechanical Durability	30 Mcycles
Minimum Switching Current	5 mA
Minimum Switching Voltage	17 V
Non-Overlap Time	1.5 ms on de-energisation no overlap between NC and NO contact 1.5 ms on energisation no overlap between NC and NO contact
Insulation Resistance	> 10 MOhm
Connections - Terminals	screw clamp terminals 1 0.000.00 in ² (12.5 mm ²)flexible with cable end screw clamp terminals 1 0.000.00 in ² (12.5 mm ²)flexible without cable end screw clamp terminals 2 0.000.00 in ² (12.5 mm ²)flexible with cable end screw clamp terminals 2 0.000.00 in ² (12.5 mm ²)flexible without cable end screw clamp terminals 1 0.000.00 in ² (12.5 mm ²)flexible without cable end screw clamp terminals 2 0.000.00 in ² (12.5 mm ²)flexible without cable end screw clamp terminals 2 0.000.00 in ² (12.5 mm ²)rigid
Tightening Torque	15.05 lbf.in (1.7 N.m) flat Ø 6 mm 15.05 lbf.in (1.7 N.m) Philips No 2 15.05 lbf.in (1.7 N.m) pozidriv No 2
Height	1.89 in (48 mm)
Width	1.02 in (26 mm)
Depth	1.65 in (42 mm)
Color	Dark grey

Environment

Environmental Characteristic	Normal environment
Ip Degree Of Protection	IP20 conforming to IEC 60529
Protective Treatment	TH IEC 60068
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Ambient Air Temperature For Operation	23140 °F (-560 °C)
Operating Altitude	9842.52 ft (3000 m)

Ordering and shipping details

Category	US10I1222341	
Discount Schedule	0112	
Gtin	3389110383850	
Returnability	No	
Country Of Origin	FR	

Packing Units

Unit Type Of Package 1PCENumber Of Units In Package 11Package 1 Height1.18 in (3.000 cm)Package 1 Width1.57 in (4.000 cm)Package 1 Length1.97 in (5.000 cm)Package 1 Weight1.21 oz (34.300 g)Unit Type Of Package 2S02Number Of Units In Package 2160Package 2 Height5.91 in (15.000 cm)	0	
Package 1 Height1.18 in (3.000 cm)Package 1 Width1.57 in (4.000 cm)Package 1 Length1.97 in (5.000 cm)Package 1 Weight1.21 oz (34.300 g)Unit Type Of Package 2S02Number Of Units In Package 2160	Unit Type Of Package 1	PCE
Package 1 Width 1.57 in (4.000 cm) Package 1 Length 1.97 in (5.000 cm) Package 1 Weight 1.21 oz (34.300 g) Unit Type Of Package 2 S02 Number Of Units In Package 2 160	Number Of Units In Package 1	1
Package 1 Length 1.97 in (5.000 cm) Package 1 Weight 1.21 oz (34.300 g) Unit Type Of Package 2 S02 Number Of Units In Package 2 160	Package 1 Height	1.18 in (3.000 cm)
Package 1 Weight 1.21 oz (34.300 g) Unit Type Of Package 2 S02 Number Of Units In Package 2 160	Package 1 Width	1.57 in (4.000 cm)
Unit Type Of Package 2 S02 Number Of Units In Package 2 160	Package 1 Length	1.97 in (5.000 cm)
Number Of Units In Package 2 160	Package 1 Weight	1.21 oz (34.300 g)
- · · · · · · · · · · · · · · · · · · ·	Unit Type Of Package 2	S02
Package 2 Height 5.91 in (15.000 cm)	Number Of Units In Package 2	160
	Package 2 Height	5.91 in (15.000 cm)

Package 2 Width	11.81 in (30.000 cm)	
Package 2 Length	15.75 in (40.000 cm)	
Package 2 Weight	12.67 lb(US) (5.746 kg)	
Unit Type Of Package 3	P06	
Number Of Units In Package 3	2560	
Package 3 Height	29.53 in (75.000 cm)	
Package 3 Width	31.50 in (80.000 cm)	
Package 3 Length	23.62 in (60.000 cm)	
Package 3 Weight	220.31 lb(US) (99.933 kg)	

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations