# **Product data sheet**

Specification





IEC contactor, TeSys Deca, nonreversing, 200A resistive, 4 pole, 4 NO, 24VDC coil, open style

LC1D115004BD

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 673.00 USD

### Main

Range	TeSys
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Resistive load
Utilisation Category	AC-1 AC-3 AC-3e AC-4
Poles Description	4P
[Ue] Rated Operational Voltage	Power circuit <= 1000 V AC 25400 Hz Power circuit <= 460 V DC
[le] Rated Operational Current	200 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit
[Uc] Control Circuit Voltage	24 V DC

### Complementary

Compatibility Code	LC1D
Pole Contact Composition	4 NO
Protective Cover	With
[Ith] Conventional Free Air Thermal Current	200 A (at 140 °F (60 °C)) for power circuit
Irms Rated Making Capacity	1260 A at 440 V for power circuit conforming to IEC 60947
Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947
[lcw] Rated Short-Time Withstand Current	250 A 104 °F (40 °C) - 10 min for power circuit 550 A 104 °F (40 °C) - 1 min for power circuit 950 A 104 °F (40 °C) - 10 s for power circuit 1100 A 104 °F (40 °C) - 1 s for power circuit
Associated Fuse Rating	250 A gG at <= 690 V coordination type 1 for power circuit 200 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	0.6 mOhm - Ith 200 A 50 Hz for power circuit
Power Dissipation Per Pole	24 W AC-1
[Ui] Rated Insulation Voltage	Power circuit 600 V CSA Power circuit 600 V UL Power circuit 1000 V IEC 60947-4-1
Overvoltage Category	III

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	8 kV IEC 60947
Safety Reliability Level	B10d = 684932 cycles contactor with nominal load EN/ISO 13849-1 B10d = 10000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	8 Mcycles
Electrical Durability	0.8 Mcycles 200 A AC-1 <= 440 V
Control Circuit Type	DC standard
Coil Technology	With integral suppression device
Control Circuit Voltage Limits	0.751.2 Uc -40131 °F (-4055 °C) operational DC 0.150.4 Uc -40158 °F (-4070 °C) drop-out DC 11.2 Uc 131158 °F (5570 °C) operational DC
Inrush Power In W	270365 W 68 °F (20 °C))
Hold-In Power Consumption In W	2.45.1 W 68 °F (20 °C)
Operating Time	2035 ms closing 4075 ms opening
Time Constant	25 ms
Maximum Operating Rate	1200 cyc/h 140 °F (60 °C)
Connections - Terminals	Control circuit: screw clamp terminals 2 0.000.00 in² (12.5 mm²) - cable stiffness: flexible with cable end  Control circuit: screw clamp terminals 1 0.000.00 in² (12.5 mm²) - cable stiffness: flexible with cable end  Control circuit: screw clamp terminals 1 0.000.00 in² (12.5 mm²) - cable stiffness: flexible without cable end  Control circuit: screw clamp terminals 2 0.000.00 in² (12.5 mm²) - cable stiffness: flexible without cable end  Control circuit: screw clamp terminals 1 0.000.00 in² (12.5 mm²) - cable stiffness: solid without cable end  Control circuit: screw clamp terminals 2 0.000.00 in² (12.5 mm²) - cable stiffness: solid without cable end  Power circuit: screw clamp terminals 2 0.000.00 in² (12.5 mm²) - cable stiffness: solid without cable end  Power circuit: connector 1 0.020.19 in² (10120 mm²) - cable stiffness: flexible without cable end  Power circuit: connector 1 0.020.19 in² (10120 mm²) - cable stiffness: flexible with cable end  Power circuit: connector 2 0.020.08 in² (1050 mm²) - cable stiffness: flexible with cable end  Power circuit: connector 1 0.020.19 in² (10120 mm²) - cable stiffness: flexible with cable end  Power circuit: connector 2 0.020.08 in² (1050 mm²) - cable stiffness: solid without cable end  Power circuit: connector 1 0.020.19 in² (10120 mm²) - cable stiffness: solid without cable end
Tightening Torque	Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals flat Ø 6 mm Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals Philips No 2 Power circuit 106.21 lbf.in (12 N.m) connector hexagonal 0.16 in (4 mm) Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals pozidriv No 2
Mounting Support	Rail Plate

### **Environment**

Standards CSA C22.2 No 1

CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508

Product Certifications	RINA
	GOST
	GL
	CCC
	DNV
	BV
	CSA
	UL
	<del>-</del>
	LROS (Lloyds register of shipping)
	UKCA
Ip Degree Of Protection	IP20 front face IEC 60529
Protective Treatment	THIEC 60068-2-30
Climatic Withstand	IACS E10 exposure to damp heat
	IEC 60947-1 Annex Q category D exposure to damp heat
	ILO 00947-1 Allilex & Category D exposure to damp fleat
Permissible Ambient Air	-40140 °F (-4060 °C)
Temperature Around The Device	140158 °F (6070 °C) with derating
	- To100 T (0070 0) Will defaultly
Operating Altitude	09842.52 ft (03000 m)
Fire Resistance	1562 °F (850 °C) IEC 60695-2-1
- The Resistance	1302 F (630 C) IEC 60093-2-1
Flame Retardance	V1 conforming to UL 94
Machanical Debuggara	NEL 6
Mechanical Robustness	Vibrations contactor open 2 Gn, 5300 Hz)
	Vibrations contactor closed 4 Gn, 5300 Hz)
	Shocks contactor closed 15 Gn for 11 ms)
	Shocks contactor open 6 Gn for 11 ms)
Height	6.22 in (158 mm)
Width	5.91 in (150 mm)
Depth	5.20 in (132 mm)
Net Weight	6.31 lb(US) (2.86 kg)

## Ordering and shipping details

Category	US10l1222359
Discount Schedule	0112
Gtin	3389110857245
Returnability	No
Country Of Origin	CZ

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.61 in (16.8 cm)
Package 1 Width	8.35 in (21.2 cm)
Package 1 Length	7.28 in (18.5 cm)
Package 1 Weight	6.06 lb(US) (2.75 kg)

### **Contractual warranty**

### Sustainability Screen Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



#### **Certifications & Standards**

REACh Declaration
Compliant with Exemptions
China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
End of Life Information
WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov