# Product data sheet

Specifications





# Contactor, TeSys Deca, 3P(3NO), AC-3/AC-3e, <=440V, 115A , 220V AC 60 Hz coil, screw clamp terminals

LC1D115M6

() Discontinued

() Discontinued on: Jul 12, 2021

#### Main

Range	TeSys
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Resistive load Motor control
Utilisation Category	AC-3 AC-1 AC-4
Poles Description	3P
[Ue] Rated Operational Voltage	Power circuit <= 1000 V AC 25400 Hz Power circuit <= 300 V DC
[le] Rated Operational Current	200 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit 115 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit
[Uc] Control Circuit Voltage	220 V AC 60 Hz

## Complementary

Motor Power Kw	30 kW at 220230 V AC 50/60 Hz (AC-3) 55 kW at 380400 V AC 50/60 Hz (AC-3) 59 kW at 415440 V AC 50/60 Hz (AC-3) 75 kW at 500 V AC 50/60 Hz (AC-3) 80 kW at 660690 V AC 50/60 Hz (AC-3) 65 kW at 1000 V AC 50/60 Hz (AC-3) 18.5 kW at 400 V AC 50/60 Hz (AC-4)	
Maximum Horse Power Rating	30 hp at 200/208 V AC 50/60 Hz for 3 phase motors 40 hp at 230/240 V AC 50/60 Hz for 3 phase motors 75 hp at 460/480 V AC 50/60 Hz for 3 phase motors 100 hp at 575/600 V AC 50/60 Hz for 3 phase motors	
Compatibility Code	LC1D	
Pole Contact Composition	3 NO	
Protective Cover	With	
[Ith] Conventional Free Air Thermal Current	200 A (at 140 °F (60 °C)) for power circuit	
Irms Rated Making Capacity	1260 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1	
Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

[Icw] Rated Short-Time Withstand Current	250 A 104 °F (40 °C) - 10 min for power circuit 550 A 104 °F (40 °C) - 1 min for power circuit 950 A 104 °F (40 °C) - 10 s for power circuit
	1100 A 104 °F (40 °C) - 1 s for power circuit $1100 \text{ A } 104 \text{ °F}$ (40 °C) - 1 s for power circuit
	100 A - 1 s for signalling circuit
	120 A - 500 ms for signalling circuit
	140 A - 100 ms for signalling circuit
Associated Fuse Rating	250 A gG at <= 690 V coordination type 1 for power circuit
-	200 A gG at <= 690 V coordination type 2 for power circuit
	10 A gG for signalling circuit
Average Impedance	0.6 mOhm - Ith 200 A 50 Hz for power circuit
Power Dissipation Per Pole	24 W AC-1
	7.9 W AC-3
[Ui] Rated Insulation Voltage	Power circuit 600 V CSA
	Power circuit 600 V UL
	Power circuit 1000 V IEC 60947-4-1
	Signalling circuit 690 V IEC 60947-1
	Signalling circuit 600 V CSA
	Signalling circuit 600 V UL
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	8 kV IEC 60947
Safety Reliability Level	B10d = 684932 cycles contactor with nominal load EN/ISO 13849-1
	B10d = 10000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	8 Mcycles
Electrical Durability	0.8 Mcycles 200 A AC-1 <= 440 V
	0.95 Mcycles 115 A AC-3 <= 440 V
Control Circuit Type	AC 60 Hz
Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	0.851.1 Uc -40131 °F (-4055 °C) operational AC 60 Hz
5	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 60 Hz
	11.1 Uc 131158 °F (5570 °C) operational AC 60 Hz
Inrush Power In Va	300 VA 60 Hz cos phi 0.8 (at 68 °F (20 °C))
Hold-In Power Consumption In Va	22 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat Dissipation	38 W at 60 Hz
Operating Time	620 ms opening
	2050 ms closing
Maximum Operating Pate	0400
Maximum Operating Rate	2400 cyc/h 140 °F (60 °C)

Connections - Terminals	Control circuit: screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) - cable stiffness: flexible with cable end	
	Control circuit: screw clamp terminals 1 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) - cable stiffness: flexible with cable end	
	Control circuit: screw clamp terminals 1 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) - cable stiffness: flexible without cable end	
	Control circuit: screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) - cable stiffness: flexible without cable end	
	Control circuit: screw clamp terminals 1 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) - cable stiffness: solid without cable end	
	Control circuit: screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) - cable stiffness: solid without cable end	
	Power circuit: connector 1 0.020.19 in <sup>2</sup> (10120 mm <sup>2</sup> ) - cable stiffness: flexible without cable end	
	Power circuit: connector 2 0.020.08 in <sup>2</sup> (1050 mm <sup>2</sup> ) - cable stiffness: flexible without cable end	
	Power circuit: connector 1 0.020.19 in <sup>2</sup> (10120 mm <sup>2</sup> ) - cable stiffness: flexible with cable end	
	Power circuit: connector 2 0.020.08 in <sup>2</sup> (1050 mm <sup>2</sup> ) - cable stiffness: flexible with cable end	
	Power circuit: connector 1 0.020.19 in <sup>2</sup> (10120 mm <sup>2</sup> ) - cable stiffness: solid without cable end	
	Power circuit: connector 2 0.020.08 in <sup>2</sup> (1050 mm <sup>2</sup> ) - cable stiffness: solid without cable end	
Tightening Torque	Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals flat Ø 6 mm Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals Philips No 2 Power circuit 106.21 lbf.in (12 N.m) connector hexagonal 0.16 in (4 mm)	
Auxiliary Contact Composition	1 NO + 1 NC	
Auxiliary Contacts Type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1	
Signalling Circuit Frequency	25400 Hz	
Minimum Switching Voltage	17 V for signalling circuit	
Minimum Switching Current	5 mA for signalling circuit	
Insulation Resistance	> 10 MOhm for signalling circuit	
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
Mounting Support	Plate Rail	

# Environment

Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Product Certifications	GOST BV CCC CSA RINA UL GL DNV LROS (Lloyds register of shipping)
Ip Degree Of Protection	IP20 front face IEC 60529
Protective Treatment	THIEC 60068-2-30
Climatic Withstand	IACS E10 exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat
Permissible Ambient Air Temperature Around The Device	-40140 °F (-4060 °C) 140158 °F (6070 °C) with derating
Operating Altitude	09842.52 ft (03000 m)

-		
Fire Resistance	1562 °F (850 °C) IEC 60695-2-1	
Flame Retardance	V1 conforming to UL 94	
Mechanical Robustness	Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor closed 15 Gn for 11 ms) Shocks contactor open 6 Gn for 11 ms)	
Height	6.22 in (158 mm)	
Width	4.72 in (120 mm)	
Depth	5.35 in (136 mm)	
Net Weight	5.51 lb(US) (2.5 kg)	

# Ordering and shipping details

Category	22359-CTR,TESYS D,OPEN,80-150A AC&DC
Discount Schedule	112
Gtin	3389110377163
Returnability	No
Country Of Origin	CZ

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.61 in (16.8 cm)
Package 1 Width	8.19 in (20.8 cm)
Package 1 Length	7.28 in (18.5 cm)
Package 1 Weight	5.34 lb(US) (2.42 kg)

#### **Contractual warranty**

Warranty

18 months

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov