# Product data sheet

Specifications





IEC contactor, TeSys Deca, nonreversing, 115A, 75HP at 480VAC, up to 100kA SCCR, 3 phase, 3 NO, 415VAC 50/60Hz coil, open

LC1D115N7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 479.00 USD

#### Main

Range	TeSys	
Range Of Product	TeSys Deca	
Product Or Component Type	Contactor	
Device Short Name	LC1D	
Contactor Application	Motor control Resistive load	
Utilisation Category	AC-4 AC-3 AC-1 AC-3e	
Poles Description	3P	
[Ue] Rated Operational Voltage	Power circuit <= 1000 V AC 25400 Hz Power circuit <= 300 V DC	
[le] Rated Operational Current	200 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit 115 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 115 A (at <140 °F (60 °C)) at <= 440 V AC AC-3e for power circuit	
[Uc] Control Circuit Voltage	415 V AC 50/60 Hz	

### Complementary

Protective Cover	With	
Pole Contact Composition	3 NO	
Compatibility Code	LC1D	
	100 hp at 575/600 V AC 50/60 Hz for 3 phase motors	
	75 hp at 460/480 V AC 50/60 Hz for 3 phase motors	
maximum florse rower rating	40 hp at 230/240 V AC 50/60 Hz for 3 phase motors	
Maximum Horse Power Rating	30 hp at 200/208 V AC 50/60 Hz for 3 phase motors	
	65 kW at 1000 V AC 50/60 Hz (AC-3e)	
	80 kW at 660690 V AC 50/60 Hz (AC-3e)	
	75 kW at 500 V AC 50/60 Hz (AC-3e)	
	59 kW at 415440 V AC 50/60 Hz (AC-3e)	
	55 kW at 380400 V AC 50/60 Hz (AC-3e)	
	30 kW at 220230 V AC 50/60 Hz (AC-3e)	
	18.5 kW at 400 V AC 50/60 Hz (AC-4)	
	80 kW at 660690 V AC 50/60 Hz (AC-3) 65 kW at 1000 V AC 50/60 Hz (AC-3)	
	75 kW at 500 V AC 50/60 Hz (AC-3)	
	59 kW at 415440 V AC 50/60 Hz (AC-3)	
	55 kW at 380400 V AC 50/60 Hz (AC-3)	
Motor Power Kw	30 kW at 220230 V AC 50/60 Hz (AC-3)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

[Ith] Conventional Free Air Thermal Current	200 A (at 140 °F (60 °C)) for power circuit
Irms Rated Making Capacity	1260 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947
[lcw] Rated Short-Time Withstand Current	250 A 104 °F (40 °C) - 10 min for power circuit 550 A 104 °F (40 °C) - 1 min for power circuit 950 A 104 °F (40 °C) - 10 s for power circuit 1100 A 104 °F (40 °C) - 1 s for power circuit 1100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Associated Fuse Rating	250 A gG at <= 690 V coordination type 1 for power circuit 200 A gG at <= 690 V coordination type 2 for power circuit 10 A gG for signalling circuit
Average Impedance	0.6 mOhm - Ith 200 A 50 Hz for power circuit
Power Dissipation Per Pole	24 W AC-1 7.9 W AC-3 7.9 W AC-3e
[Ui] Rated Insulation Voltage	Power circuit 600 V CSA Power circuit 600 V UL Power circuit 1000 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-1 Signalling circuit 600 V CSA Signalling circuit 600 V UL
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	8 kV IEC 60947
Safety Reliability Level	B10d = 684932 cycles contactor with nominal load EN/ISO 13849-1 B10d = 10000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	8 Mcycles
Electrical Durability	0.8 Mcycles 200 A AC-1 <= 440 V 0.95 Mcycles 115 A AC-3 <= 440 V 0.95 Mcycles 115 A AC-3e <= 440 V
Control Circuit Type	AC 50/60 Hz
Coil Technology	Built-in bidirectional peak limiting diode suppressor
Control Circuit Voltage Limits	0.30.5 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.15 Uc -40131 °F (-4055 °C) operational AC 50/60 Hz 11.15 Uc 131158 °F (5570 °C) operational AC 50/60 Hz
Inrush Power In Va	280350 VA 60 Hz cos phi 0.8 (at 68 °F (20 °C)) 280350 VA 50 Hz cos phi 0.8 (at 68 °F (20 °C))
Hold-In Power Consumption In Va	218 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 218 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat Dissipation	38 W at 50/60 Hz
Operating Time	620 ms opening 2050 ms closing
Maximum Operating Rate	2400 cyc/h 140 °F (60 °C)

Connections - Terminals	Control circuit: screw clamp terminals 2 0.000.00 in² (12.5 mm²) - cable stiffness:
	flexible with cable end  Control circuit: screw clamp terminals 1 0.000.00 in² (12.5 mm²) - cable stiffness:
	flexible with cable end
	Control circuit: screw clamp terminals 1 $0.000.00$ in $^2$ $(12.5$ mm $^2)$ - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 2 0.000.00 in² (12.5 mm²) - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 1 0.000.00 in² (12.5 mm²) - cable stiffness: solid without cable end
	Control circuit: screw clamp terminals 2 0.000.00 in² (12.5 mm²) - cable stiffness: solid without cable end
	Power circuit: connector 1 0.020.19 in² (10120 mm²) - cable stiffness: flexible without cable end
	Power circuit: connector 2 0.020.08 in² (1050 mm²) - cable stiffness: flexible without cable end
	Power circuit: connector 1 0.020.19 in² (10120 mm²) - cable stiffness: flexible with cable end
	Power circuit: connector 2 0.020.08 in² (1050 mm²) - cable stiffness: flexible with cable end
	Power circuit: connector 1 0.020.19 in² (10120 mm²) - cable stiffness: solid
	without cable end Power circuit: connector 2 0.020.08 in² (1050 mm²) - cable stiffness: solid
	without cable end
Tightening Torque	Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals flat Ø 6 mm
	Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals Philips No 2 Power circuit 106.21 lbf.in (12 N.m) connector hexagonal 0.16 in (4 mm)
	Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals pozidriv No 2
Auxiliary Contact Composition	1 NO + 1 NC
Auxiliary Contacts Type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Signalling Circuit Frequency	25400 Hz
Minimum Switching Voltage	17 V for signalling circuit
Minimum Switching Current	5 mA for signalling circuit
Insulation Resistance	> 10 MOhm for signalling circuit
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Mounting Support	Rail Plate
Environment	
Standards	CSA C22.2 No 14
	EN 60947-4-1
	EN 60947-5-1
	IEC 60947-4-1 IEC 60947-5-1
	UL 508
Product Certifications	ccc
	UL
	RINA BV
	GOST
	CSA
	DNV
	LROS (Lloyds register of shipping) GL
	UKCA
	CE
Ip Degree Of Protection	IP20 front face IEC 60529
Protective Treatment	THIEC 60068-2-30
Climatic Withstand	IACS E10 exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat
	• • • • • • • • • • • • • • • • • • •

Permissible Ambient Air Temperature Around The Device	-40140 °F (-4060 °C) 140158 °F (6070 °C) with derating
Operating Altitude	09842.52 ft (03000 m)
Fire Resistance	1562 °F (850 °C) IEC 60695-2-1
Flame Retardance	V1 conforming to UL 94
Mechanical Robustness	Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor closed 15 Gn for 11 ms) Shocks contactor open 6 Gn for 11 ms)
Height	6.22 in (158 mm)
Width	4.72 in (120 mm)
Depth	5.35 in (136 mm)
Net Weight	5.51 lb(US) (2.5 kg)

# Ordering and shipping details

Category	US10I1222359
Discount Schedule	0112
Gtin	3389110377200
Returnability	No
Country Of Origin	CZ

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.61 in (16.8 cm)
Package 1 Width	8.19 in (20.8 cm)
Package 1 Length	7.28 in (18.5 cm)
Package 1 Weight	5.34 lb(US) (2.42 kg)

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



### **Certifications & Standards**

REACh Declaration
Compliant with Exemptions
China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
End of Life Information
WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov