Product data sheet

Specifications





TeSys Deca contactor - 4P(2 NO + 2 NC) - AC-1 - <= 440 V 25 A - 48 V DC coil

LC1D1286ED

(!) Discontinued

Main

Range	TeSys
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Resistive load
Utilisation Category	AC-1 AC-3 AC-3e AC-4
Poles Description	4P
[Ue] Rated Operational Voltage	Power circuit <= 690 V AC 25400 Hz Power circuit <= 300 V DC
[le] Rated Operational Current	25 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit
[Uc] Control Circuit Voltage	48 V DC

Complementary

Complementary	
Compatibility Code	LC1D
Pole Contact Composition	2 NO + 2 NC
Protective Cover	With
[Ith] Conventional Free Air Thermal Current	25 A (at 140 °F (60 °C)) for power circuit 10 A (at 140 °F (60 °C)) for signalling circuit
	10 A (at 140 F (60 C)) for signalling circuit
Irms Rated Making Capacity	250 A at 440 V for power circuit conforming to IEC 60947
	140 A AC for signalling circuit conforming to IEC 60947-5-1
	250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated Breaking Capacity	250 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand	105 A 104 °F (40 °C) - 10 s for power circuit
Current	210 A 104 °F (40 °C) - 1 s for power circuit
	30 A 104 °F (40 °C) - 10 min for power circuit
	61 A 104 °F (40 °C) - 1 min for power circuit
	100 A - 1 s for signalling circuit
	120 A - 500 ms for signalling circuit
	140 A - 100 ms for signalling circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1
	40 A gG at <= 690 V coordination type 1 for power circuit
	25 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit
Power Dissipation Per Pole	1.56 W AC-1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

[Ui] Rated Insulation Voltage	Power circuit 690 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL Signalling circuit 690 V IEC 60947-1 Signalling circuit 600 V CSA Signalling circuit 600 V UL
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	30 Mcycles
Electrical Durability	0.8 Mcycles 25 A AC-1 <= 440 V
Control Circuit Type	DC standard
Coil Technology	With integral suppression device
Control Circuit Voltage Limits	0.10.25 Uc -40158 °F (-4070 °C) drop-out DC 0.71.25 Uc -40140 °F (-4060 °C) operational DC 11.25 Uc 140158 °F (6070 °C) operational DC
Inrush Power In W	5.4 W 68 °F (20 °C))
Hold-In Power Consumption In W	5.4 W 68 °F (20 °C)
Operating Time	53.5572.45 ms closing 1624 ms opening
Time Constant	28 ms
Maximum Operating Rate	3600 cyc/h 140 °F (60 °C)
Connections - Terminals	Control circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm) Power circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm)
Tightening Torque	Control circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 6 mm M3.5 Control circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 8 mm M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5
Auxiliary Contact Composition	1 NO + 1 NC
Auxiliary Contacts Type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Signalling Circuit Frequency	25400 Hz
Minimum Switching Voltage	17 V for signalling circuit
Minimum Switching Current	5 mA for signalling circuit
Insulation Resistance	> 10 MOhm for signalling circuit
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Mounting Support	Plate Rail

Environment

Standards

CSA C22.2 No 14

EN 60947-4-1

EN 60947-5-1

IEC 60947-4-1

IEC 60947-5-1

UL 508

DNV GOST LROS (Lloyds register of shipping) RINA UL GL CSA CCC BV	-	
LROS (Lloyds register of shipping) RINA UL GL CSA CCC BV Ip Degree Of Protection IP20 front face IEC 60529 Protective Treatment THIEC 60068-2-30 Climatic Withstand IACS E10 exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat One of the composition of the protection of the composition of the comp	Product Certifications	DNV
RINA UL GL CSA CCC BV		GOST
RINA UL GL CSA CCC BV		LROS (Lloyds register of shipping)
GL		1 2 2
GL		UL
Post		
Protective Treatment		
Ip Degree Of Protection IP20 front face IEC 60529 Protective Treatment THIEC 60068-2-30 Climatic Withstand IACS E10 exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat Permissible Ambient Air Temperature Around The Device -76176 °F (-6080 °C) storage -40140 °F (-4060 °C) operation 140158 °F (6070 °C) with derating Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor open 10 Gn for 11 ms) Shocks contactor open 10 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)		
Post		
Protective Treatment THIEC 60068-2-30 Climatic Withstand IACS E10 exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat Permissible Ambient Air Temperature Around The Device -76176 °F (-6080 °C) storage -40140 °F (-4060 °C) operation 140158 °F (6070 °C) with derating Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)		DV
Climatic Withstand IACS E10 exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat Permissible Ambient Air Temperature Around The Device -76176 °F (-6080 °C) storage -40140 °F (-4060 °C) operation 140158 °F (6070 °C) with derating Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)	Ip Degree Of Protection	IP20 front face IEC 60529
IEC 60947-1 Annex Q category D exposure to damp heat	Protective Treatment	THIEC 60068-2-30
Permissible Ambient Air Temperature Around The Device -76176 °F (-6080 °C) storage -40140 °F (-4060 °C) operation 140158 °F (6070 °C) with derating Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)	Climatic Withstand	IACS F10 exposure to damp heat
Permissible Ambient Air Temperature Around The Device -76176 °F (-6080 °C) storage -40140 °F (-4060 °C) operation 140158 °F (6070 °C) with derating Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)		·
Temperature Around The Device -40140 °F (-4060 °C) operation 140158 °F (6070 °C) with derating Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)		120 000 17 17 minox & outogory 15 exposure to dump hout
Temperature Around The Device -40140 °F (-4060 °C) operation 140158 °F (6070 °C) with derating Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)	Permissible Ambient Air	-76176 °F (-6080 °C) storage
Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Vibrations contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)	Temperature Around The Device	
Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)		· · · · · · · · · · · · · · · · · · ·
Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)		(
Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)	Operating Altitude	09842.52 ft (03000 m)
Mechanical Robustness Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)	Fire Resistance	1562 °F (850 °C) IEC 60695-2-1
Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)	Flame Retardance	V1 conforming to UL 94
Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)	Mechanical Robustness	Vibrations contactor open 2 Gn. 5300 Hz)
Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)		· · · · · · · · · · · · · · · · · · ·
Shocks contactor closed 15 Gn for 11 ms) Height		
Height 3.35 in (85 mm) Width 1.77 in (45 mm) Depth 3.90 in (99 mm)		·
Width 1.77 in (45 mm) Depth 3.90 in (99 mm)		Should contacte discourse contact that the
Depth 3.90 in (99 mm)	Height	3.35 in (85 mm)
	Width	1.77 in (45 mm)
Net Weight 1 16 lb(US) (0.525 kg)	Depth	3.90 in (99 mm)
is(is)	Net Weight	1.16 lb(US) (0.525 kg)

Ordering and shipping details

Category	22355-CTR,TESYS D,OPEN,9-38A DC
Discount Schedule	112
Gtin	3389110403558
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Contractual warranty

Warranty	18 months		
----------	-----------	--	--



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Mercury Free	
⊘	Rohs Exemption Information	Yes
⊘	Pvc Free	

Certifications & Standards

Eu Rohs Directive	Compliant	
	EU RoHS Declaration	
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	