## Product data sheet

Specifications





① Discontinued

### IEC contactor, TeSys Deca, nonreversing, 60A resistive, 4 pole, 4 NO, 48VAC 50/60Hz coil, open style

LC1DT60AE7

() Discontinued on: Apr 19, 2023

# Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Range	TeSys TeSys Deca
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Resistive load
Utilisation Category	AC-1
Poles Description	4P
[Ue] Rated Operational Voltage	Power circuit <= 690 V AC 25400 Hz Power circuit <= 300 V DC
[le] Rated Operational Current	60 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit
[Uc] Control Circuit Voltage	48 V AC 50/60 Hz

### Complementary

Compatibility Code	LC1D	
Pole Contact Composition	4 NO	
Protective Cover	With	
[Ith] Conventional Free Air	10 A (at 140 °F (60 °C)) for signalling circuit	
Thermal Current	60 A (at 140 °F (60 °C)) for power circuit	
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1	
	250 A DC for signalling circuit conforming to IEC 60947-5-1	
	800 A at 440 V for power circuit conforming to IEC 60947	
Rated Breaking Capacity	800 A at 440 V for power circuit conforming to IEC 60947	
[Icw] Rated Short-Time Withstand	320 A 104 °F (40 °C) - 10 s for power circuit	
Current	720 A 104 °F (40 °C) - 1 s for power circuit	
	72 A 104 °F (40 °C) - 10 min for power circuit	
	165 A 104 °F (40 °C) - 1 min for power circuit	
	100 A - 1 s for signalling circuit	
	120 A - 500 ms for signalling circuit	
	140 A - 100 ms for signalling circuit	
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1	
	80 A gG at <= 690 V coordination type 1 for power circuit	
	80 A gG at <= 690 V coordination type 2 for power circuit	
Average Impedance	1.6 mOhm - Ith 60 A 50 Hz for power circuit	
Power Dissipation Per Pole	5.8 W AC-1	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

[Ui] Rated Insulation Voltage	Power circuit 600 V CSA
	Power circuit 600 V UL
	Signalling circuit 690 V IEC 60947-1 Signalling circuit 600 V CSA
	Signalling circuit 600 V UL
	Power circuit 690 V IEC 60947-4-1
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	6 Mcycles
Electrical Durability	1.4 Mcycles 60 A AC-1 <= 440 V
Control Circuit Type	AC 50/60 Hz
Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz
	0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz
	0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz
Inrush Power In Va	140 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 160 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))
Hold-In Power Consumption In Va	13 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 15 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat Dissipation	45 W at 50/60 Hz
Operating Time	419 ms opening 1226 ms closing
Maximum Operating Rate	3600 cyc/h 140 °F (60 °C)
Connections - Terminals	Control circuit: screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) - cable stiffness: flexible with cable end
	Control circuit: screw clamp terminals 1 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> ) - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 2 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> ) - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 1 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> ) - cable stiffness:
	flexible with cable end Control circuit: screw clamp terminals 1 0.000.01 in² (14 mm²) - cable stiffness:
	solid without cable end
	Control circuit: screw clamp terminals 2 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> ) - cable stiffness: solid without cable end
	Power circuit: screw clamp terminal 1 0.000.05 in <sup>2</sup> (135 mm <sup>2</sup> ) - cable stiffness:
	flexible without cable end Power circuit: screw clamp terminal 2 0.000.04 in² (125 mm²) - cable stiffness:
	flexible without cable end
	Power circuit: screw clamp terminal 1 0.000.05 in <sup>2</sup> (135 mm <sup>2</sup> ) - cable stiffness: flexible with cable end Deuter circuit: account common terminal 2 0.00. 0.04 in <sup>2</sup> (125 mm <sup>2</sup> ), cable stiffness:
	Power circuit: screw clamp terminal 2 0.000.04 in <sup>2</sup> (125 mm <sup>2</sup> ) - cable stiffness: flexible with cable end
	Power circuit: screw clamp terminal 1 0.000.05 in <sup>2</sup> (135 mm <sup>2</sup> ) - cable stiffness: solid without cable end
	Power circuit: screw clamp terminal 2 0.000.04 in <sup>2</sup> (125 mm <sup>2</sup> ) - cable stiffness: solid without cable end
Tightening Torque	Control circuit 15.05 lbf.in (1.7 N.m) EverLink BTR screw connectors flat Ø 6 mm
	Control circuit 15.05 lbf.in (1.7 N.m) EverLink BTR screw connectors Philips No 2
	Power circuit 70.81 lbf.in (8 N.m) EverLink BTR screw connectors 0.040.05 in <sup>2</sup>
	(2535 mm²) hexagonal 0.16 in (4 mm) Power circuit 44.25 lbf.in (5 N.m) EverLink BTR screw connectors 0.000.04 in² (1
	25 mm <sup>2</sup> ) hexagonal 0.16 in (4 mm)
	Control circuit 15.05 lbf.in (1.7 N.m) EverLink BTR screw connectors pozidriv No 2 Power circuit 22.13 lbf.in (2.5 N.m) EverLink BTR screw connectors pozidriv No 2
Auxiliary Contact Composition	1 NO + 1 NC

Auxiliary Contacts Type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1	
Signalling Circuit Frequency	25400 Hz	
Minimum Switching Voltage	17 V for signalling circuit	
Minimum Switching Current	5 mA for signalling circuit	
Insulation Resistance	> 10 MOhm for signalling circuit	
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
Mounting Support	Rail Plate	

#### Environment

Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1
	IEC 60947-4-1
	IEC 60947-5-1
	UL 508
	IEC 60335-1
Product Certifications	RINA
	GL
	DNV
	CSA
	BV
	LROS (Lloyds register of shipping)
	GOST
	UL
	CCC
Ip Degree Of Protection	IP20 front face IEC 60529
Protective Treatment	THIEC 60068-2-30
Climatic Withstand	IACS E10 exposure to damp heat
	IEC 60947-1 Annex Q category D exposure to damp heat
Permissible Ambient Air	-40140 °F (-4060 °C)
Temperature Around The Device	140158 °F (6070 °C) with derating
Our annahim an Alkita al a	
Operating Altitude	09842.52 ft (03000 m)
Fire Resistance	1562 °F (850 °C) IEC 60695-2-1
Flame Retardance	V1 conforming to UL 94
Mechanical Robustness	Vibrations contactor open 2 Gn, 5300 Hz)
	Vibrations contactor closed 4 Gn, 5300 Hz)
	Shocks contactor closed 15 Gn for 11 ms)
	Shocks contactor open 10 Gn for 11 ms)
Height	4.80 in (122 mm)
Width	2.76 in (70 mm)
Depth	4.72 in (120 mm)
Net Weight	2.40 lb(US) (1.09 kg)

## Ordering and shipping details

Category	US10I1222357
Discount Schedule	0112
Gtin	3389119409254
Returnability	No

Life Is On Scheider

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.07 in (7.8 cm)
Package 1 Width	5.31 in (13.5 cm)
Package 1 Length	5.98 in (15.2 cm)
Package 1 Weight	2.40 lb(US) (1.087 kg)

### **Contractual warranty**

Warranty

18 months

### Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov