# Product data sheet

Specifications





() Discontinued

### TeSys F contactor - 3P (3 NO) -AC-3 - <= 440 V 115 A - coil 120 V AC

LC1F115G6

() Discontinued on: Feb 17, 2021

Product availability: Non-Stock - Not normally stocked in distribution facility

### Main

Range	TeSys	
Range Of Product	TeSys F	
Product Or Component Type	Contactor	
Device Short Name	LC1F	
Contactor Application	Motor control Resistive load	
Utilisation Category	AC-3 AC-4 AC-1	
Poles Description	3P	
[Ue] Rated Operational Voltage	<= 690 V AC 50/60 Hz <= 460 V DC	
[Uc] Control Circuit Voltage	120 V AC 60 Hz	
[Ie] Rated Operational Current	200 A (at <104 °F (40 °C)) at <= 440 V AC-1 115 A (at <131 °F (55 °C)) at <= 440 V AC-3	

### Complementary

[Uimp] Rated Impulse Withstand Voltage	8 KV
[Ith] Conventional Free Air Thermal Current	200 A (at 104 °F (40 °C))
Rated Breaking Capacity	920 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	1100 A 104 °F (40 °C) - 10 s 640 A 104 °F (40 °C) - 30 s 520 A 104 °F (40 °C) - 1 min 400 A 104 °F (40 °C) - 3 min 320 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	125 A aM at <= 440 V 200 A gG at <= 440 V
Average Impedance	0.37 mOhm - Ith 200 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power Dissipation Per Pole	15 W AC-1 5 W AC-3
Overvoltage Category	III
Power Pole Contact Composition	3 NO

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Motor Power Kw	55 kW at 380400 V AC 50/60 Hz (AC-3)
	59 kW at 415 V AC 50/60 Hz (AC-3)
	59 kW at 440 V AC 50/60 Hz (AC-3)
	75 kW at 500 V AC 50/60 Hz (AC-3)
	80 kW at 660690 V AC 50/60 Hz (AC-3)
	30 kW at 220230 V AC 50/60 Hz (AC-3)
	18.5 kW at 400 V AC 50/60 Hz (AC-4)
Control Circuit Voltage Limits	Operational 0.851.1 Uc 50/60 Hz 131 °F (55 °C))
ç	Drop-out 0.350.55 Uc 50/60 Hz 131 °F (55 °C))
Mechanical Durability	10 Mcycles
Inrush Power In Va	660 VA, 60 Hz 0.3 68 °F (20 °C))
Hold-In Power Consumption In Va	55 VA, 60 Hz 0.3 68 °F (20 °C))
Maximum Operating Rate	2400 cyc/h 131 °F (55 °C)
Operating Time	2335 ms closing 515 ms opening
Connections - Terminals	Power circuit bar 2 20 x 3 mm
	Power circuit lugs-ring terminals 1 0.15 in <sup>2</sup> (95 mm <sup>2</sup> )
	Power circuit connector 1 0.15 in <sup>2</sup> (95 mm <sup>2</sup> )
	Control circuit screw clamp terminals 1 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )flexible without
	cable end
	Control circuit screw clamp terminals 2 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )flexible without
	cable end
	Control circuit screw clamp terminals 1 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )flexible with cable
	Control circuit screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> )flexible with cable
	end
	Control circuit screw clamp terminals 1 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )solid without cable end
	Control circuit screw clamp terminals 2 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )solid without cable
	end
	Power circuit bolted connection
Tightening Torque	Power circuit 88.51 lbf.in (10 N.m)
	Control circuit 10.62 lbf.in (1.2 N.m)
Mounting Support	Plate
Heat Dissipation	1216 W
Standards	IEC 60947-4-1
	IEC 60947-1
	EN 60947-1
	JIS C8201-4-1
	EN 60947-4-1
Product Certifications	ABS
	BV
	UL
	RINA
	LROS (Lloyds register of shipping)
	RMRoS
	CCC
	DNV
	СВ
Compatibility Code	LC1F
Control Circuit Type	AC 60 Hz

### Environment

Ip Degree Of Protection	IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106
Protective Treatment	тн
Ambient Air Temperature For Operation	-40140 °F (-4060 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Permissible Ambient Air Temperature Around The Device	140…158 °F (60…70 °C) at Uc

Height	6.38 in (162 mm)
Width	6.43 in (163.3 mm)
Depth	6.73 in (171 mm)
Operating Altitude	9842.52 ft (3000 m) without derating
Net Weight	7.56 lb(US) (3.43 kg)

# Ordering and shipping details

Category	US10I1222336	
Discount Schedule	0112	
Gtin	3389110122220	
Returnability	No	
Country Of Origin	CZ	

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.27 in (21 cm)
Package 1 Width	7.87 in (20 cm)
Package 1 Length	9.45 in (24 cm)
Package 1 Weight	9.15 lb(US) (4.152 kg)

### **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free

Rohs Exemption Information

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov